

For installation of Tango cylindrical and square wall down light LED.
Model. UTA-31821 and UTA-31841.

Product drawing (dimensions)

UTA-31821 UTA-31841

SUITABLE FOR WET LOCATIONS

MOUNTING DETAIL

TOOL

NOTE
Mounts over a 3" Octagonal Junction box.

①

②

③

④

Using the nylon washers and the 7mm. nut driver secure the back plate to the wall

↑ UP

Ensure watertight seal using UL approved silicone based sealant.

⑤

Connect Power and Ground Wire.

⑥

Notice to installer :

- 1.WIRING INSTRUCTIONS** Warning : RISK OF FIRE AND ELECTRICAL SHOCK. : FIXTURE MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN ONLY>FIXTURE IS INTENDED FOR INSTALLATION IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, LOCAL AND FEDERAL CODE SPECIFICATIONS. DISCONNECT POWER BEFORE SERVICING.
- 2.This fixture has a VOLTAGE SPECIFIC BALLAST,**Check that the supply voltage is the same as the installed ballast voltage.

Ligman Lighting USA

7144 NW Progress Court, Hillsboro
Oregon, 97124, USA
Tel : 503 645 0500 | Fax : 503 645 8100

www.ligmanlightingusa.com

UTA-31821/30/08/14/REV.0
1/1



FM-TS-13/25-05-2007-REV.2