



For installation of Tango wall surface luminaire LED
Model. UTA-31861, UTA-31871, UTA-31881 and UTA-31891.


Product drawing (dimensions) SUITABLE FOR WET LOCATIONS




NOTE
Mounts over
a 3" Octagonal
Junction box.



①



②




③

Using the nylon washers
and the 7mm. nut driver
secure the back
plate to the wall

Ensure watertight seal using UL
approved silicone based sealant.




④



⑤

Connect Power
and Ground Wire.



⑥

Notice to installer :

- 1. WIRING INSTRUCTIONS** Warning : RISK OF FIRE AND ELECTRICAL SHOCK. : FIXTURE MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN ONLY>FIXTURE IS INTENDED FOR INSTALLATION IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, LOCAL AND FEDERAL CODE SPECIFICATIONS. DISCONNECT POWER BEFORE SERVICING.
- 2. This fixture has a VOLTAGE SPECIFIC BALLAST,** Check that the supply voltage is the same as the installed ballast voltage.

Ligman Lighting USA

7144 NW Progress Court, Hillsboro
Oregon, 97124, USA
Tel : 503 645 0500 | Fax : 503 645 8100

www.ligmanlightingusa.com

UTA-31861 03/02/16/REV.0
1/1



FM-TS-13/25-05-2007-REV.2