

LUMINAIRE SPECIFICATION

 Head Office:
 Tel: 503-645-0500


 7144 NW Progress Ct
 Fax: 503-645-8100

 Hillsboro, Oregon 97124
 www.ligmanlightingusa.com

IP65 : Suitable for Wet Locations ULH

IK08: Impact Resistant (Vandal Resistant)







ULH-10582

Mini lightsoft bollard

A decorative range of cylindrical and square shape bollards with a symmetrical light distribution available in two standard heights. Developed to compliment the Lightsoft bollard and Mini Lightsoft wall light. Designed for lighting of entrances and residential areas by providing wide spread ground illumination on driveways, pathways and squares. The innovative reflector technology of the Mini Lightsoft bollard guarantees a high degree of efficiency and optimal visual comfort while fulfilling the dark sky criteria.

Vandal resistant extruded aluminum and low copper content die cast housing with high corrosion resistance. Stainless steel screws. Durable silicone rubber gasket and clear impact resistant UV stabilized polycarbonate diffuser. Ballast is enclosed in an internal waterproof capsule. Housing is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral control gear. Anodized high purity aluminum reflector.

 $\hfill\Box$ 02- Dark Grey - RAL 7043

□ 07- Custom - RAL

□ 04 - Metallic Silver - RAL 9006

Physical Data

Length: 4.02" Height: 39.37" Weight: 8.3 lbs

Lamp

□ T4 CMH 20w 1 ===

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)

Voltage (Please Specify)

- □ 120V
- □ 277V
- $\ \square$ Other $_$

Options (Please Specify)

Color (Please Specify)

- □ 01-Black RAL 9011
- □ 03-White RAL 9003
- □ 05-Matt Silver RAL 9006
- □ 06-Bronze RAL 6014
 - 03 04



Mounting Accessories



☐ Anchor Bolt Kit





Ordering Example: ULH - 10582 - T4-CMH-20w - 120v



PROJECT:

PE: QUANTITY:

NOTE:

DATE: _____

