


LUMINAIRE SPECIFICATION

IP55 : Suitable for Wet Locations

IK07 : Impact Resistant (Vandal Resistant)





ø2.99"x4.5



Ordering Example : UMA - 97066 - HPS-2x400w - 120v - Options

PROJECT:

Rev: 11/13

UMA-97066 Mar 6 double large streetlight type II

A small size cylindrical shape street light using metal halide or high pressure sodium lamps 70-150w. High quality reflector designs provide options of a broad light distribution or forward throw distribution. The luminaires are suitable for downward lighting at a 5 degree tilt. Designed for lighting private roadways, modern street suburbs and city centers.

Aluminum frame and body. Stainless steel screws and hardware. Durable silicone rubber gasket and impact resistant toughened glass diffuser with hinged aluminum frame for in-position lamp replacement. The luminaire is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral control gear. Anodized high purity aluminum reflector. Mar 1 and 2 fit over the top of a 3" tenon.

Physical Data Length: 66.4" Height: 12.4" Weight: 91.0 lbs

Lamp

□ HPS-ED18 2x400w 🖙

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)

Voltage (Please Specify)

□ 120V

□ 277V


Other _

Options (Please Specify)

Color (Please Specify)

□ 01-Black - RAL 9011 □ 03-White - RAL 9003 □ 05-Matt Silver - RAL 9006 □ 06-Bronze - RAL 6014

- 02- Dark Grey RAL 7043
- □ 04 Metallic Śilver RAL 9006
- □ 07- Custom RAL _____



□ Straight arm 0° tilt (Dark sky compliant)



QUANTITY: NOTE:





 TYPE:
 QUANTITY:
 NOTE:

 Ligman Lighting USA reserves the right to change specifications without prior notice, please contact factory for latest information.
 Due to the continual improvements in LED technology data and components may change without notice.