

LUMINAIRE SPECIFICATION

 Head Office:
 Tel: 503-645-0500

 7144 NW Progress Ct
 Fax: 503-645-8100

 Hillsboro, Oregon 97124
 www.ligmanlightingusa.com

IP55 : Suitable for Wet Locations
IK07 : Impact Resistant (Vandal Resistant)



UMA-97072

Mar 7 single area light type IV

A small size cylindrical shape street light using metal halide or high pressure sodium lamps 70-150w. High quality reflector designs provide options of a broad light distribution or forward throw distribution. The luminaires are suitable for downward lighting at a 5 degree tilt. Designed for lighting private roadways, modern street suburbs and city centers.

Aluminum frame and body. Stainless steel screws and hardware. Durable silicone rubber gasket and impact resistant toughened glass diffuser with hinged aluminum frame for in-position lamp replacement. The luminaire is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral control gear. Anodized high purity aluminum reflector. Mar 1 and 2 fit over the top of a 3" tenon.

Physical Data

Length: 35.1" Height: 12.4" Weight: 39.6 lbs

Lamp

□ PMH-T15 250w **■**

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)

Voltage (Please Specify)


- □ 120V
- □ 277V
- □ Other _____

Options (Please Specify)

Color (Please Specify)

- □ 01-Black RAL 9011 □ 03-White - RAL 9003
- □ 02- Dark Grey RAL 7043□ 04 Metallic Silver RAL 9006
- □ 05-Matt Silver RAL 9006
- □ 07- Custom RAL
- □ 06-Bronze RAL 6014





☐ Straight arm 0° tilt (Dark sky compliant)





Ordering Example: UMA - 97072 - PMH-250w - 120v - Options



PROJECT:

PE: QUANTITY:

NOTE:

_ DATE: _____

