


LUMINAIRE SPECIFICATION

Head Office:
7144 NW Progress Ct
Hillsboro, Oregon 97124
Tel: 503-645-0500
Fax: 503-645-8100
www.ligmanlightingusa.com

IP55 : Suitable for Wet Locations
IK07 : Impact Resistant (Vandal Resistant)







UMA-97073

Mar 7 single area light type IV

A small size cylindrical shape street light using metal halide or high pressure sodium lamps 70-150w. High quality reflector designs provide options of a broad light distribution or forward throw distribution. The luminaires are suitable for downward lighting at a 5 degree tilt. Designed for lighting private roadways, modern street suburbs and city centers.

Aluminum frame and body. Stainless steel screws and hardware. Durable silicone rubber gasket and impact resistant toughened glass diffuser with hinged aluminum frame for in-position lamp replacement. The luminaire is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral control gear. Anodized high purity aluminum reflector. Mar 1 and 2 fit over the top of a 3″ tenon.

Physical Data

Length: 35.1″
Height: 12.4″
Weight: 43.8 lbs

Lamp

☐ PMH-T15 320w

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)


Voltage (Please Specify)


☐ 120V
☐ 277V
☐ Other _____

Options (Please Specify)


Color (Please Specify)

☐ 01-Black - RAL 9011
☐ 03-White - RAL 9003
☐ 05-Matt Silver - RAL 9006
☐ 06-Bronze - RAL 6014
☐ 02- Dark Grey - RAL 7043
☐ 04 - Metallic Silver - RAL 9006
☐ 07- Custom - RAL _____





☐ Straight arm 0˚ tilt (Dark sky compliant)





Ordering Example : UMA - 97073 - PMH-320w - 120v - Options

PROJECT: _____ DATE: _____

TYPE: _____ QUANTITY: _____ NOTE: _____

Ligman Lighting USA reserves the right to change specifications without prior notice, please contact factory for latest information.
Due to the continual improvements in LED technology data and components may change without notice.