

LUMINAIRE SPECIFICATION

Head Office: Tel: 503-645-0500 7144 NW Progress Ct Fax: 503-645-8100 Hillsboro, Oregon 97124 www.ligmanlightingusa.com

IP55 : Suitable for Wet Locations IK07 : Impact Resistant (Vandal Resistant)



UMA-97076 Mar 7 single area light type IV

A small size cylindrical shape street light using metal halide or high pressure sodium lamps 70-150w. High quality reflector designs provide options of a broad light distribution or forward throw distribution. The luminaires are suitable for downward lighting at a 5 degree tilt. Designed for lighting private roadways, modern street suburbs and city centers.

Aluminum frame and body. Stainless steel screws and hardware. Durable silicone rubber gasket and impact resistant toughened glass diffuser with hinged aluminum frame for in-position lamp replacement. The luminaire is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral control gear. Anodized high purity aluminum reflector. Mar 1 and 2 fit over the top of a 3" tenon.

Physical Data Length: 35.1" Height: 12.4" Weight: 43.8 lbs

Lamp

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)

Voltage (Please Specify)


- □ 120V
- □ 277V
- Other

Options (Please Specify)

Color (Please Specify)

- □ 01-Black RAL 9011 D 03-White - RAL 9003
- □ 02- Dark Grey RAL 7043
- □ 04 Metallic Śilver RAL 9006
- D 07- Custom RAL





□ Straight arm 0° tilt (Dark sky compliant)









Due to the continual improvements in LED technology data and components may change without notice.