
# LUMINAIRE SPECIFICATION

Head Office:
7144 NW Progress Ct
Hillsboro, Oregon 97124
Tel: 503-645-0500
Fax: 503-645-8100
www.ligmanlightingusa.com

IP54 : Suitable for Wet Locations
IK07 : Impact Resistant (Vandal Resistant)






# UTR-96025

## Triangle 4 double small area light type IV

A small size triangle design street light luminaire using metal halide lamps or high pressure sodium lamps 70-150w. A high quality cut-off reflector design creates broad spread light distribution. Designed for lighting of private roadways, modern street suburbs and city centers.
Aluminum frame and body. Stainless steel screws and hardware. Durable silicone rubber gasket and impact resistant toughened glass diffuser with hinged aluminum frame for in-position lamp replacement. The luminaire is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral control gear. Anodized high purity aluminum reflector.

### Physical Data

Length: 49.3″
Height: 20.2″
Weight: 40.5 lbs

### Lamp

☐ HPS-ED17 2x100w

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)


### Voltage (Please Specify)


☐ 120V
☐ 277V
☐ Other _____

### Options (Please Specify)

Color (Please Specify)

☐ 01-Black - RAL 9011
☐ 02- Dark Grey - RAL 7043
☐ 03-White - RAL 9003
☐ 04 - Metallic Silver - RAL 9006
☐ 05-Matt Silver - RAL 9006
☐ 07- Custom - RAL _____
☐ 06-Bronze - RAL 6014






*Ordering Example : UTR - 96025 - HPS-2x100w - 120v - Options*

PROJECT: _____ DATE: _____

TYPE: _____ QUANTITY: _____ NOTE: _____

Rev: 11/13

Ligman Lighting USA reserves the right to change specifications without prior notice, please contact factory for latest information.
Due to the continual improvements in LED technology data and components may change without notice.

Intertek