LUMINAIRE SPECIFICATION

Head Office:
7144 NW Progress Ct
Hillsboro, Oregon 97124
Tel: 503-645-0500
Fax: 503-645-8100
www.ligmanlightingusa.com

IP54 : Suitable for Wet Locations
IK07 : Impact Resistant (Vandal Resistant)



UMN-92226-SC60

Martini 4 medium single area light type II

Small and medium size modern shape area light distribution for metal halide lamps or sodium vapour discharge lamps 70-400w and LED. A high quality reflector design creates broad spread light distribution. Main application for lighting of public, private roadways, car parks, exhibition areas, service stations, truck stop and sports grounds. Aluminium housing with high corrosion resistance. Integral control gear. Stainless steel screws. Durable silicone rubber gasket and clear toughened glass with hinge aluminium frame for in-position lamp replacement. Anodized high purity aluminium reflector. Main housing is powder paint with high corrosion resistance with chemical chromatized protection.

Physical Data

Length: 26.8″
Height: 7″
Weight: 26.2 lbs

Lamp

☐ HPS-ED18 250w

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)


Voltage (Please Specify)

☐ 120V
☐ 277V
☐ Other _____

Options (Please Specify)


Color (Please Specify)

☐ 01-Black - RAL 9011
☐ 02- Dark Grey - RAL 7043
☐ 03-White - RAL 9003
☐ 04 - Metallic Silver - RAL 9006
☐ 05-Matt Silver - RAL 9006
☐ 07- Custom - RAL _____
☐ 06-Bronze - RAL 6014



☐ Frosted Lens

☐ Clear Lens






☐ Straight Arm 0° Tilt (Dark Sky Compliant)





☐ Single Banner Arm ☐ Double Banner Arm



Ordering Example : UMN - 92226-SC60 - HPS-250w - 120v - Options

PROJECT: _____ DATE: _____

TYPE: _____ QUANTITY: _____ NOTE: _____

Ligman Lighting USA reserves the right to change specifications without prior notice, please contact factory for latest information.
Due to the continual improvements in LED technology data and components may change without notice.