

# LUMINAIRE SPECIFICATION


UQU-31353

Head Office: Tel: 503-645-0500 Fax: 503-645-8100 7144 NW Progress Ct Hillsboro, Oregon 97124 www.ligmanlightingusa.com


## IP65 : Suitable for Wet Locations IK09 : Impact Resistant (Vandal Resistant)














Mounting detail





Ordering Example : UQU - 31353 - PMH-70w - 120v - Options

#### Low copper content corrosion resistant die-cast aluminum frame and body. Stainless steel screws and anodized high purity 95% reflective aluminum reflector. Durable silicone rubber gasket and impact resistant toughened glass diffuser. The luminaire is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral electronic control gear. For mounting in upward or

building facades.



downward positions

Lamp

□ PMH-ED17 70w 🔍 (For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)

Quarter 2 asymmetrical wall washer

A small and large size guarter-cylindrical wall mounted luminaire with a selection of energy saving compact fluorescent and metal halide and high pressure sodium lamps. Light output is finely controlled to minimize light pollution with three types of light distribution. Namely, asymmetrical forward throw, symmetrical downward light distribution and side throw light distribution. Flat toughened glass cover for

minimum spill light. Designed for the illumination of entrances, terraces, corridors and

### Voltage (Please Specify)

□ 120V

□ 277V

□ Other \_\_\_

## Options (Please Specify)

Color (Please Specify)

- D 01-Black RAL 9011
- 🗆 03-White RAL 9003
- D 05-Matt Silver RAL 9006
- □ 06-Bronze RAL 6014
- □ 02- Dark Grey RAL 7043
- □ 04 Metallic Śilver RAL 9006
- 07- Custom RAL







□ SCE - Surface Conduit Entry Box - □ 1/2" Conduit □ 3/4" Conduit

