


LUMINAIRE SPECIFICATION


Head Office: Tel: 503-645-0500 7144 NW Progress Ct Fax: 503-645-8100

Hillsboro, Oregon 97124 www.ligmanlightingusa.com

IP55: Suitable for Wet Locations IK07: Impact Resistant (Vandal Resistant)







Mounting detail



UMA-30887

Mar 5 wall wash area light

A cylindrical shaped wall mount area light with cut-off light distribution for metal halide or high pressure sodium lamps 70-150w. High quality reflector design provides options of a broad light distribution or forward throw distribution. The luminaires are suitable for downward lighting at a 5 degree tilt using a classical arm bracket. Designed for lighting footpaths, car parks, building façades, under canopies and roadways.

Single cable entry. Low copper content corrosion resistant die-cast aluminum frame and body. Stainless steel screws. Durable silicone rubber gasket and impact resistant toughened glass diffuser with hinged aluminum frame for in-position lamp replacement. The luminaire is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral control gear. Anodized high purity 95% reflective aluminum reflector.

Physical Data

Length: 25.28" Height: 10.24" Weight: 41.0 lbs

Lamp

□ HPS-ED17 100w

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)

Voltage (Please Specify)

- □ 120V
- □ 277V
- □ Other _

Options (Please Specify)

- ☐ F Frosted Lens
- □ C Clear Lens

Color (Please Specify)

- □ 01-Black RAL 9011
- □ 03-White RAL 9003
- □ 05-Matt Silver RAL 9006
- □ 02- Dark Grey RAL 7043 □ 04 - Metallic Śilver - RAL 9006 □ 07- Custom - RAL
- □ 06-Bronze RAL 6014













□ 0 Degree Tilt



Ordering Example: UMA - 30887 - HPS-100w - 120v - Options



PROJECT:

QUANTITY:

NOTE:

DATE: _

