


LUMINAIRE SPECIFICATION

Head Office: Tel: 503-645-0500 7144 NW Progress Ct Fax: 503-645-8100 Hillsboro, Oregon 97124 www.ligmanlightingusa.com

IP54 : Suitable for Wet Locations IK07 : Impact Resistant (Vandal Resistant)









Ordering Example : UTR - 32074 - HPS-70w - 120v - Options

Rev: 11/13

UTR-32074

Triangle small wall area light type IV

A small size triangle design wall mounted area light luminaire using metal halide, high pressure sodium lamps 70-150w and LED. A high quality optic design creates broad spread light distribution. Designed for lighting footpaths, car parks, building facades, under canopies and roadways. The LED luminaires have features such as long life, limited maintenance and constant lifetime performance.

Aluminum frame and body. Stainless steel screws and hardware. Durable silicone rubber gasket and impact resistant tempered glass diffuser with hinged aluminum frame for in-position lamp replacement. The luminaire is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral control gear. Anodized high purity aluminum reflector.

Physical Data

Length: 23.6" Height: 20.2" Weight: 20.9 lbs

Lamp

□ HPS-ED17 70w 🔍

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)

Voltage (Please Specify)

□ 120V

□ 277V


□ Other _

Options (Please Specify)

Color (Please Specify)

01-Black - RAL 9011
03-White - RAL 9003
05-Matt Silver - RAL 9006
06-Bronze - RAL 6014

- 02- Dark Grey RAL 7043
- D 04 Metallic Śilver RAL 9006
- □ 07- Custom RAL _____





SAM - Small Adjustable Arm



Due to the continual improvements in LED technology data and components may change without notice.