LUMINAIRE SPECIFICATION

Head Office:
7144 NW Progress Ct
Hillsboro, Oregon 97124
Tel: 503-645-0500
Fax: 503-645-8100
www.ligmanlightingusa.com

IP54 : Suitable for Wet Locations
IK07 : Impact Resistant (Vandal Resistant)



UTR-32075


Triangle small wall area light type IV


A small size triangle design wall mounted area light luminaire using metal halide, high pressure sodium lamps 70-150w and LED. A high quality optic design creates broad spread light distribution. Designed for lighting footpaths, car parks, building facades, under canopies and roadways. The LED luminaires have features such as long life, limited maintenance and constant lifetime performance.

Aluminum frame and body. Stainless steel screws and hardware. Durable silicone rubber gasket and impact resistant tempered glass diffuser with hinged aluminum frame for in-position lamp replacement. The luminaire is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral control gear. Anodized high purity aluminum reflector.

Physical Data

Length: 23.6″
Height: 20.2″
Weight: 22.4 lbs





Mounting detail

Lamp

☐ HPS-ED17 100w

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)


Voltage (Please Specify)


☐ 120V
☐ 277V
☐ Other _____

Options (Please Specify)

Color (Please Specify)


☐ 01-Black - RAL 9011
☐ 02- Dark Grey - RAL 7043
☐ 03-White - RAL 9003
☐ 04 - Metallic Silver - RAL 9006
☐ 05-Matt Silver - RAL 9006
☐ 07- Custom - RAL _____
☐ 06-Bronze - RAL 6014





☐ SAM - Small Adjustable Arm

Mounting detail for adjustable arm





Ordering Example : UTR - 32075 - HPS-100w - 120v - Options

PROJECT: _____ DATE: _____

TYPE: _____ QUANTITY: _____ NOTE: _____

Rev: 11/13

Ligman Lighting USA reserves the right to change specifications without prior notice, please contact factory for latest information.
Due to the continual improvements in LED technology data and components may change without notice.