

LUMINAIRE SPECIFICATION


Tel: 503-645-0500 7144 NW Progress Ct Fax: 503-645-8100 Hillsboro, Oregon 97124

www.ligmanlightingusa.com

IP54: Suitable for Wet Locations

IK07: Impact Resistant (Vandal Resistant)









UTR-32076

Triangle small wall area light type IV

A small size triangle design wall mounted area light luminaire using metal halide, high pressure sodium lamps 70-150w and LED. A high quality optic design creates broad spread light distribution. Designed for lighting footpaths, car parks, building facades, under canopies and roadways. The LED luminaires have features such as long life, limited maintenance and constant lifetime performance.

Aluminum frame and body. Stainless steel screws and hardware. Durable silicone rubber gasket and impact resistant tempered glass diffuser with hinged aluminum frame for in-position lamp replacement. The luminaire is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral control gear. Anodized high purity aluminum reflector.

Physical Data

Length: 23.6" Height: 20.2" Weight: 22.4 lbs

Lamp

□ HPS-ED17 150w **■**

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)


Voltage (Please Specify)

- □ 120V
- □ 277V
- □ Other _

Options (Please Specify)

Color (Please Specify)

- □ 01-Black RAL 9011
- □ 03-White RAL 9003 □ 05-Matt Silver - RAL 9006
- □ 06-Bronze RAL 6014
- □ 02- Dark Grey RAL 7043
- □ 04 Metallic Śilver RAL 9006 □ 07- Custom - RAL



□ SAM - Small Adjustable Arm



Ordering Example: UTR - 32076 - HPS-150w - 120v - Options



PROJECT:

QUANTITY:

NOTE:

DATE: _

