


LUMINAIRE SPECIFICATION


Head Office: Tel: 503-645-0500 7144 NW Progress Ct Fax: 503-645-8100 Hillsboro, Oregon 97124 www.ligmanlightingusa.com

IP65 : Suitable for Wet Locations IK08 : Impact Resistant (Vandal Resistant)





Mounting detail



3" Mounting Plate

4" Mounting Plate



Ordering Example : UGI - 31081 - T4-40w - 120v - Options

Rev: 11/13

	PROJECT:			_ DATE:
	TYPE:	QUANTITY:	NOTE:	
	Ligman Lighting USA reserves the right to change specifications without prior notice, please contact factory for latest information. Due to the continual improvements in LED technology data and components may change without notice.			

UGI-31081 Gipo 2 clear diffu

Gino 2 clear diffuser

Wall mounted luminaires with upward and downward light distributions. Ideally suited to illuminate the wall and surfaces in front of wall and for light accents on vertical surfaces using halogen main voltage or compact fluorescent lamps.

Low copper content corrosion resistant die-cast aluminum frame and body. Stainless steel screws. Durable silicone rubber gasket and impact resistant toughened glass diffuser The luminaire is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral control gear. Anodized high purity 95% reflective aluminum reflector. As an option the glass lens can be lightly frosted to hide lamp image. The Gino can also be supplied in a LED version. Fixture mounts over a 3" octagonal junction box

Physical Data

Length: 3.94" Height: 3.91" Weight: 1.98 lbs

Lamp

□ T4 CAPSULE 40w 120v =

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)

Voltage (Please Specify)

□ 120V

Color (Please Specify)

- □ 01-Black RAL 9011
 □ 03-White RAL 9003
 □ 05-Matt Silver RAL 9006
- 02- Dark Grey RAL 7043
- □ 04 Metallic Silver RAL 9006 □ 07- Custom - RAL



Options (Please Specify)

- F Frosted Lens
- C Clear Lens

Spike Beam (Optional)

Single Spike

Mounting Detail (Please Specify) □ 3" Mounting Plate

□ 4" Mounting Plate



Intertek