



Matrix 1, 2, 3 square wall up-down light


IP65 ◆ ▲ ▲ /EN 60598/CLASS I Ⓢ /▽/CE/IK08



Suitable for wet locations


Wall mounted compact cubic luminaires with up and downward light distributions using one lamp mounted in the horizontal position. The Matrix is designed with three options of light distributions. Using high efficiency and long life lamps. Designed to illuminate the wall and surface in front of wall and for light accents on vertical or horizontal surfaces. The LED luminaires have features such as long life, limited maintenance and constant lifetime performance.

Low copper content corrosion resistant die-cast aluminum frame and body. Stainless steel screws. Durable silicone rubber gasket and impact resistant toughened glass diffuser. The luminaire is treated with a chemical chromated protection before powder coating, ensuring high corrosion resistance. To maintain the integrity of the IP rating of this luminaire it is supplied with a specially designed SHG self sealing wiring grommet that is used when connecting to the power supply. This grommet insures that water and dust does not enter the luminaire through the knockout hole in the back of the luminaire. Integral control gear.




Product Family





UMT-31392






Matrix 1 square wall up-down light


Model No.	Lamp	Holder	Beam	Lumen	Weight
UMT-31391	T4 HALOGEN 100w. 120v.	MINI-CAN	3.5°/77°	1800	4.8 lb.
UMT-31392	T4 CMH 20w.	GU6.5	5.0°/82°	1615	4.8 lb.
UMT-31393	T4 CMH 39w.	GU6.5	5.0°/82°	2450	4.8 lb.
UMT-31394	T4.5 CMH 39w.	G8.5	5.0°/82°	2720	4.8 lb.

Matrix 1 square wall up-down light HP LED

Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UMT-31395-N-W27	1Up/7Down	615 lm	2700K	6Up/12Down	3.5°/19°	4.6 lb.	•
UMT-31395-N-W30	1Up/7Down	655 lm	3000K	6Up/12Down	3.5°/19°	4.6 lb.	•
UMT-31395-N-W40	1Up/7Down	663 lm	4000K	6Up/12Down	3.5°/19°	4.6 lb.	•
UMT-31395-M-W27	1Up/7Down	607 lm	2700K	6Up/12Down	3.5°/25°	4.6 lb.	•
UMT-31395-M-W30	1Up/7Down	646 lm	3000K	6Up/12Down	3.5°/25°	4.6 lb.	•
UMT-31395-M-W40	1Up/7Down	660 lm	4000K	6Up/12Down	3.5°/25°	4.6 lb.	•
UMT-31395-W-W27	1Up/7Down	594 lm	2700K	6Up/12Down	3.5°/34°	4.6 lb.	•
UMT-31395-W-W30	1Up/7Down	632 lm	3000K	6Up/12Down	3.5°/34°	4.6 lb.	•
UMT-31395-W-W40	1Up/7Down	640 lm	4000K	6Up/12Down	3.5°/34°	4.6 lb.	•



UMT-31402







Matrix 2 square wall up-down light

Model No.	Lamp	Holder	Beam	Lumen	Weight
UMT-31401	T4 HALOGEN 100w. 120v.	MINI-CAN	3.5°/3.5°	1800	4.8 lb.
UMT-31402	T4 CMH 20w.	GU6.5	5.0°/5.0°	1615	4.8 lb.
UMT-31403	T4 CMH 39w.	GU6.5	5.0°/5.0°	2450	4.8 lb.
UMT-31404	T4.5 CMH 39w.	G8.5	5.0°/5.0°	2720	4.8 lb.


Matrix 2 square wall up-down light HP LED

Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UMT-31405-W27	2 LED	116 lm	2700K	17	5°	4.8 lb.	•
UMT-31405-W30	2 LED	124 lm	3000K	17	5°	4.8 lb.	•
UMT-31405-W40	2 LED	128 lm	4000K	17	5°	4.8 lb.	•





UMT-31412







Matrix 3 square wall up-down light

Model No.	Lamp	Holder	Beam	Lumen	Weight
UMT-31411	T4 HALOGEN 100w. 120v.	MINI-CAN	77°/77°	1800	4.8 lb.
UMT-31412	T4 CMH 20w.	GU6.5	82°/82°	1615	4.8 lb.
UMT-31413	T4 CMH 39w.	GU6.5	82°/82°	2450	4.8 lb.
UMT-31414	T4.5 CMH 39w.	G8.5	82°/82°	2720	4.8 lb.

Matrix 3 square wall up-down light HP LED

Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UMT-31415-N-W27	2x7 LED	2x561 lm	2700K	24	19°	4.8 lb.	•
UMT-31415-N-W30	2x7 LED	2x597 lm	3000K	24	19°	4.8 lb.	•
UMT-31415-N-W40	2x7 LED	2x603 lm	4000K	24	19°	4.8 lb.	•
UMT-31415-M-W27	2x7 LED	2x553 lm	2700K	24	25°	4.8 lb.	•
UMT-31415-M-W30	2x7 LED	2x588 lm	3000K	24	25°	4.8 lb.	•
UMT-31415-M-W40	2x7 LED	2x600 lm	4000K	24	25°	4.8 lb.	•
UMT-31415-W-W27	2x7 LED	2x539 lm	2700K	24	34°	4.8 lb.	•
UMT-31415-W-W30	2x7 LED	2x574 lm	3000K	24	34°	4.8 lb.	•
UMT-31415-W-W40	2x7 LED	2x579 lm	4000K	24	34°	4.8 lb.	•





LIGMAN

The quality of life...

Outdoor Lighting Solutions.

www.ligman.com



Matrix 4 square wall down light







IP65 ◆ ▲ ▲ /EN 60598/CLASS I Ⓢ /V/CE /IK08




Suitable for wet locations

Wall mounted compact cubic luminaires with a downward light distribution using one lamp mounted in the horizontal position. The Matrix uses high efficiency and long life lamps. Designed to illuminate the wall and surface in front of wall and for light accents on vertical or horizontal surfaces. The LED luminaires have features such as long life, limited maintenance and constant lifetime performance.

Low copper content corrosion resistant die-cast aluminum frame and body. Stainless steel screws. Durable silicone rubber gasket and impact resistant toughened glass diffuser. The luminaire is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. To maintain the integrity of the IP rating of this luminaire it is supplied with a specially designed SHG self sealing wiring grommet that is used when connecting to the power supply. This grommet insures that water and dust does not enter the luminaire through the knockout hole in the back of the luminaire. Integral control gear.

					
- 01. Black RAL 9011	- 02. Dark Grey RAL 7043	- 03. White RAL 9003	- 04. Metalic Silver RAL 9006	- 05. Matt Silver RAL 9006	- 06. Bronze RAL 6014


Product Family




P.253 Matrix 1




P.253 Matrix 2




P.254 Matrix 3



P.257 Matrix 4



UMT-31422



Matrix 4 square wall down light

Model No.	Lamp	Holder	Beam	Lumen	Weight
UMT-31421	T4 HALOGEN 100w. 120v.	MINI-CAN	77°	1800	4.8 lb.
UMT-31422	T4 CMH 20w.	GU6.5	82°	1615	4.8 lb.
UMT-31423	T4 CMH 39w.	GU6.5	82°	2450	4.8 lb.
UMT-31424	T4.5 CMH 39w.	G8.5	82°	2720	4.8 lb.

Matrix 4 square wall down light HP LED

Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UMT-31425-N-W27	7 LED	561 lm	2700K	12	19°	4.8 lb.	•
UMT-31425-N-W30	7 LED	597 lm	3000K	12	19°	4.8 lb.	•
UMT-31425-N-W40	7 LED	603 lm	4000K	12	19°	4.8 lb.	•
UMT-31425-M-W27	7 LED	552 lm	2700K	12	25°	4.8 lb.	•
UMT-31425-M-W30	7 LED	588 lm	3000K	12	25°	4.8 lb.	•
UMT-31425-M-W40	7 LED	600 lm	4000K	12	25°	4.8 lb.	•
UMT-31425-W-W27	7 LED	538 lm	2700K	12	34°	4.8 lb.	•
UMT-31425-W-W30	7 LED	573 lm	3000K	12	34°	4.8 lb.	•
UMT-31425-W-W40	7 LED	579 lm	4000K	12	34°	4.8 lb.	•

