


LUMINAIRE SPECIFICATION

Tel: 503-645-0500 7144 NW Progress Ct Fax: 503-645-8100 Hillsboro, Oregon 97124 www.ligmanlightingusa.com

IP65: Suitable for Wet Locations

IK08: Impact Resistant (Vandal Resistant)





0.98 2.36" **~**-3.54″**~**

Ø0.24"

Mounting detail



UMT-31412

Matrix 3 square wall up-down light

Wall mounted compact cubic luminaires with up and downward light distributions using one lamp mounted in the horizontal position. The Matrix is designed with three options of light distributions. Using high efficiency and long life lamps. Designed to illuminate the wall and surface in front of wall and for light accents on vertical or horizontal surfaces.

Low copper content corrosion resistant die-cast aluminum frame and body. Stainless steel screws. Durable silicone rubber gasket and impact resistant toughened glass diffuser. The luminaire is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral control gear. Anodized high purity aluminum reflector.

Physical Data

Length: 7.09" Height: 6.3" Weight: 4.8 lbs

Lamp

□ T4 CMH 20w 1 📼

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)

Voltage (Please Specify)

- □ 120V
- □ 277V
- □ Other

Options (Please Specify)

Color (Please Specify)

- □ 01-Black RAL 9011 □ 03-White - RAL 9003
- □ 02- Dark Grey RAL 7043 □ 04 - Metallic Śilver - RAL 9006 □ 05-Matt Silver - RAL 9006
 - □ 07- Custom RAL
- □ 06-Bronze RAL 6014


















DATE:

Ordering Example: UMT - 31412 - T4-20w - 120v - Options



PROJECT:

QUANTITY:

NOTE:

