
LUMINAIRE SPECIFICATION

LIGMAN LIGHTING USA

Head Office:
7144 NW Progress Ct
Hillsboro, Oregon 97124
Tel: 503-645-0500
Fax: 503-645-8100
www.ligmanlightingusa.com

IP65 : Suitable for Wet Locations
IK08 : Impact Resistant (Vandal Resistant)





UMT-31424

Matrix 4 square wall down light

Wall mounted compact cubic luminaires with up and downward light distributions using one lamp mounted in the horizontal position. The Matrix is designed with three options of light distributions. Using high efficiency and long life lamps. Designed to illuminate the wall and surface in front of wall and for light accents on vertical or horizontal surfaces.
Low copper content corrosion resistant die-cast aluminum frame and body. Stainless steel screws. Durable silicone rubber gasket and impact resistant toughened glass diffuser. The luminaire is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral control gear. Anodized high purity aluminum reflector.

Physical Data

Length: 7.09″
Height: 6.3″
Weight: 4.8 lbs

Lamp

☐ T4.5 CMH 39w

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)


Voltage (Please Specify)


☐ 120V
☐ 277V
☐ Other _____

Options (Please Specify)

Color (Please Specify)

☐ 01-Black - RAL 9011
☐ 02- Dark Grey - RAL 7043
☐ 03-White - RAL 9003
☐ 04 - Metallic Silver - RAL 9006
☐ 05-Matt Silver - RAL 9006
☐ 07- Custom - RAL _____
☐ 06-Bronze - RAL 6014









Ordering Example : UMT - 31424 - T4.5-39w - 120v - Options

PROJECT: _____ DATE: _____

TYPE: _____ QUANTITY: _____ NOTE: _____

Rev: 11/13

Ligman Lighting USA reserves the right to change specifications without prior notice, please contact factory for latest information.
Due to the continual improvements in LED technology data and components may change without notice.

Intertek