





Tango 5, 6 cylindrical surface exterior downlight dia. 6.3" , 7.32"


IP65   /EN 60598/CLASS I  //CE/IK10




Suitable for wet locations

A range of cylindrical surface mounted exterior downlight luminaires. Developed for interior and exterior lighting using a variety of different lamp options. These include compact fluorescent lamps, and discharge lamps.

Low copper content die-cast aluminum housing and aluminum bottom frame with integral anti-glare baffles. Stainless steel screws. Durable silicone rubber gasket and clear toughened glass. Single cable entry. Housing is treated with a chemical chromated protection before powder coating, ensuring high corrosion resistance. Integral control gear. Anodized high purity aluminum reflector.




Product Family



Accessories


Mounting ring for semi recessed installation of the surface mount down light



Model No.	Ceiling cut hole	For model No.
A80181	ø7.48"	UTA-80021-80022
A80281	ø8.5"	UTA-80011-80018






UTA-80022-N




Tango 5 cylindrical exterior downlight dia. 6.3"


Model No.	Lamp	Holder	Beam	Lumen	Weight	(H) Height
UTA-80021	CFQ 18w.	G24q-2	88°	1075	4.6 lb.	10.43"
UTA-80022-VN	T6 CMH 39w.	G12	6°	2720	8.1 lb.	12.0"
UTA-80022-N	T6 CMH 39w.	G12	12°	2720	8.1 lb.	12.0"
UTA-80022-M	T6 CMH 39w.	G12	26°	2720	8.1 lb.	12.0"
UTA-80022-W	T6 CMH 39w.	G12	35°	2720	8.1 lb.	12.0"
UTA-80022-VW	T6 CMH 39w.	G12	60°	2720	8.1 lb.	12.0"




Bottom view



Mounting detail






UTA-80016-VN




Tango 6 cylindrical exterior downlight dia. 7.32"

Model No.	Lamp	Holder	Beam	Lumen	Weight	(H) Height	Picture
UTA-80011	CFQ 26w./CFTR 32/42w.	Gx24q-3/4	79°/74°/79°	1550/2040/2720	6.8 lb.	11.37"	1
UTA-80012	PMH-ED17 70w.	MED	67°	4000	12.5 lb.	15.51"	2
UTA-80013	PMH-ED17 100w.	MED	67°	6500	12.7 lb.	15.51"	2
UTA-80014	HPS-ED17 70w.	MED	79°	5450	12.5 lb.	15.51"	2
UTA-80015	HPS-ED17 100w.	MED	67°	8550	12.7 lb.	16.29"	2
UTA-80016-VN	T6 CMH 70w.	G12	6°	5600	11.9 lb.	13.34"	2
UTA-80016-N	T6 CMH 70w.	G12	12°	5600	11.9 lb.	13.34"	2
UTA-80016-M	T6 CMH 70w.	G12	26°	5600	11.9 lb.	13.34"	2
UTA-80016-W	T6 CMH 70w.	G12	35°	5600	11.9 lb.	13.34"	2
UTA-80016-VW	T6 CMH 70w.	G12	60°	5600	11.9 lb.	13.34"	2
UTA-80017-VN	T6 CMH 100w.	G12	10°	7600	13.44 lb.	13.34"	2
UTA-80017-N	T6 CMH 100w.	G12	12°	7600	13.44 lb.	13.34"	2
UTA-80017-M	T6 CMH 100w.	G12	30°	7600	13.44 lb.	13.34"	2
UTA-80017-W	T6 CMH 100w.	G12	40°	7600	13.44 lb.	13.34"	2
UTA-80017-VW	T6 CMH 100w.	G12	64°	7600	13.44 lb.	13.34"	2
UTA-80018-VN	T6 CMH 150w.	G12	10°	11500	13.44 lb.	13.34"	2
UTA-80018-N	T6 CMH 150w.	G12	12°	11500	13.44 lb.	13.34"	2
UTA-80018-M	T6 CMH 150w.	G12	30°	11500	13.44 lb.	13.34"	2
UTA-80018-W	T6 CMH 150w.	G12	40°	11500	13.44 lb.	13.34"	2
UTA-80018-VW	T6 CMH 150w.	G12	64°	11500	13.44 lb.	13.34"	2




Bottom view

Picture 1



Bottom view

Picture 2



Mounting detail

(VN) Very Narrow beam

(N) Narrow beam

(M) Medium beam

(W) Wide beam

(VW) Very Wide beam



Tango 5, 6 cylindrical surface exterior downlight dia. 6.3" , 7.32" HP LED


IP65 ⚡⚡/EN 60598/CLASS I ⚡/V/CE/IK10



Suitable for wet locations

A range of cylindrical surface mounted exterior downlight luminaires. The luminaires are suitable for indoor and outdoor applications for use in residential, shopping and public areas as surface ceiling downlights. The luminaires have features such as long life, limited maintenance and constant lifetime performance.

The luminaire is rated as class I with the high power LED integral driver. Low copper content die-cast aluminium housing with a chemical chromatised protection before powder coating, ensuring high corrosion resistance. Stainless steel screws. Power is provided to the luminaire through water tight single cable gland. Durable silicone rubber gasket and clear toughened glass.




Product Family



Accessories


Mounting ring for semi recessed installation of the surface mount down light



Model No.	Ceiling cut hole	For model No.
A80181	ø7.48"	UTA-80401,UTA80315
A80281	ø8.5"	UTA-80421



UTA-80401-N




Tango 5 cylindrical surface downlight dia. 6.3" HP LED

Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UTA-80401-N-W27	18 LED	1826 lm	2700K	30	14°	6.8 lb.	•
UTA-80401-N-W30	18 LED	1943 lm	3000K	30	14°	6.8 lb.	•
UTA-80401-N-W40	18 LED	1917 lm	4000K	30	14°	6.8 lb.	•
UTA-80401-M-W27	18 LED	1781 lm	2700K	30	24°	6.8 lb.	•
UTA-80401-M-W30	18 LED	1895 lm	3000K	30	24°	6.8 lb.	•
UTA-80401-M-W40	18 LED	2072 lm	4000K	30	24°	6.8 lb.	•
UTA-80401-W-W27	18 LED	1712 lm	2700K	30	40°	6.8 lb.	•
UTA-80401-W-W30	18 LED	1822 lm	3000K	30	40°	6.8 lb.	•
UTA-80401-W-W40	18 LED	1933 lm	4000K	30	40°	6.8 lb.	•




UTA-80421-N



Tango 6 cylindrical surface downlight dia. 7.32" HP LED


Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UTA-80421-N-W27	24 LED	2392 lm	2700K	40	14°	8.1 lb.	•
UTA-80421-N-W30	24 LED	2545 lm	3000K	40	14°	8.1 lb.	•
UTA-80421-N-W40	24 LED	2750 lm	4000K	40	14°	8.1 lb.	•
UTA-80421-M-W27	24 LED	2415 lm	2700K	40	24°	8.1 lb.	•
UTA-80421-M-W30	24 LED	2570 lm	3000K	40	24°	8.1 lb.	•
UTA-80421-M-W40	24 LED	2568 lm	4000K	40	24°	8.1 lb.	•
UTA-80421-W-W27	24 LED	2295 lm	2700K	40	40°	8.1 lb.	•
UTA-80421-W-W30	24 LED	2442 lm	3000K	40	40°	8.1 lb.	•
UTA-80421-W-W40	24 LED	2488 lm	4000K	40	40°	8.1 lb.	•




Bottom view




Mounting detail




(N) Narrow beam




(M) Medium beam




(W) Wide beam




(N), (M), (W) beam in 3000K



(N), (M), (W) beam in 4000K






Bottom view



Mounting detail




UTA-80315-N




Tango cylindrical LED

Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UTA-80315-VN-W27	9 LED	817 lm	2700K	17	9°	4.8 lb.	•
UTA-80315-VN-W30	9 LED	821 lm	3000K	17	9°	4.8 lb.	•
UTA-80315-VN-W40	9 LED	939 lm	4000K	17	9°	4.8 lb.	•
UTA-80315-N-W27	9 LED	716 lm	2700K	17	13°	4.8 lb.	•
UTA-80315-N-W30	9 LED	720 lm	3000K	17	13°	4.8 lb.	•
UTA-80315-N-W40	9 LED	823 lm	4000K	17	13°	4.8 lb.	•
UTA-80315-M-W27	9 LED	751 lm	2700K	17	23°	4.8 lb.	•
UTA-80315-M-W30	9 LED	755 lm	3000K	17	23°	4.8 lb.	•
UTA-80315-M-W40	9 LED	863 lm	4000K	17	23°	4.8 lb.	•
UTA-80315-W-W27	9 LED	776 lm	2700K	17	32°	4.8 lb.	•
UTA-80315-W-W30	9 LED	780 lm	3000K	17	32°	4.8 lb.	•
UTA-80315-W-W40	9 LED	892 lm	4000K	17	32°	4.8 lb.	•





Bottom view



Mounting detail




UTA-80325-N




Tango square LED

Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UTA-80325-VN-W27	9 LED	817 lm	2700K	17	9°	6.6 lb.	•
UTA-80325-VN-W30	9 LED	821 lm	3000K	17	9°	6.6 lb.	•
UTA-80325-VN-W40	9 LED	939 lm	4000K	17	9°	6.6 lb.	•
UTA-80325-N-W27	9 LED	716 lm	2700K	17	13°	6.6 lb.	•
UTA-80325-N-W30	9 LED	720 lm	3000K	17	13°	6.6 lb.	•
UTA-80325-N-W40	9 LED	823 lm	4000K	17	13°	6.6 lb.	•
UTA-80325-M-W27	9 LED	751 lm	2700K	17	23°	6.6 lb.	•
UTA-80325-M-W30	9 LED	755 lm	3000K	17	23°	6.6 lb.	•
UTA-80325-M-W40	9 LED	863 lm	4000K	17	23°	6.6 lb.	•
UTA-80325-W-W27	9 LED	776 lm	2700K	17	32°	6.6 lb.	•
UTA-80325-W-W30	9 LED	780 lm	3000K	17	32°	6.6 lb.	•
UTA-80325-W-W40	9 LED	892 lm	4000K	17	32°	6.6 lb.	•







Bottom view



Mounting detail



Tango 15, 16 square surface exterior downlight 6.3" , 7.32"


IP65   /EN 60598/CLASS I  / /IK10



Suitable for wet locations - Vandal resistant.


A range of square surface mounted exterior downlight luminaires. Developed for interior and exterior lighting using a variety of different lamp options. These include compact fluorescent lamps, and discharge lamps.

Low copper content die-cast aluminum housing and aluminum bottom frame with integral anti-glare baffles. Stainless steel screws. Durable silicone rubber gasket and clear toughened glass. Single cable entry. Housing is treated with a chemical chromated protection before powder coating, ensuring high corrosion resistance. Integral control gear. Anodized high purity aluminum reflector.




Product Family








UTA-80142-N




Tango 15 square surface exterior downlight 6.3"

Model No.	Lamp	Holder	Beam	Lumen	Weight	(H) Height
UTA-80141	CFQ 18w.	G24q-2	88°	1075	4.8 lb.	10.43"
UTA-80142-VN	T6 CMH 39w.	G12	6°	2720	9.0 lb.	12.0"
UTA-80142-N	T6 CMH 39w.	G12	12°	2720	9.0 lb.	12.0"
UTA-80142-M	T6 CMH 39w.	G12	26°	2720	9.0 lb.	12.0"
UTA-80142-W	T6 CMH 39w.	G12	35°	2720	9.0 lb.	12.0"
UTA-80142-VW	T6 CMH 39w.	G12	60°	2720	9.0 lb.	12.0"



Bottom view




Mounting detail






UTA-80156-N

Tango 16 square surface exterior downlight 7.32"


Model No.	Lamp	Holder	Beam	Lumen	Weight	(H) Height	Picture
UTA-80151	CFQ 26w./CFTR 32/42w.	Gx24q-3/4	79°/74°/79°	1550/2040/2720	9.2 lb.	11.41"	1
UTA-80152	PMH-ED17 70w.	MED	67°	4000	14.5 lb.	15.63"	2
UTA-80153	PMH-ED17 100w.	MED	67°	6500	15.4 lb.	15.63"	2
UTA-80154	HPS-ED17 70w.	MED	79°	5450	14.5 lb.	15.63"	2
UTA-80155	HPS-ED17 100w.	MED	67°	8550	14.7 lb.	16.37"	2
UTA-80156-VN	T6 CMH 70w.	G12	6°	5600	13.8 lb.	13.42"	2
UTA-80156-N	T6 CMH 70w.	G12	12°	5600	13.8 lb.	13.42"	2
UTA-80156-M	T6 CMH 70w.	G12	26°	5600	13.8 lb.	13.42"	2
UTA-80156-W	T6 CMH 70w.	G12	35°	5600	13.8 lb.	13.42"	2
UTA-80156-VW	T6 CMH 70w.	G12	60°	5600	13.8 lb.	13.42"	2
UTA-80157-VN	T6 CMH 100w.	G12	10°	7600	15.4 lb.	13.42"	2
UTA-80157-N	T6 CMH 100w.	G12	12°	7600	15.4 lb.	13.42"	2
UTA-80157-M	T6 CMH 100w.	G12	30°	7600	15.4 lb.	13.42"	2
UTA-80157-W	T6 CMH 100w.	G12	40°	7600	15.4 lb.	13.42"	2
UTA-80157-VW	T6 CMH 100w.	G12	64°	7600	15.4 lb.	13.42"	2
UTA-80158-VN	T6 CMH 150w.	G12	10°	11500	15.4 lb.	13.42"	2
UTA-80158-N	T6 CMH 150w.	G12	12°	11500	15.4 lb.	13.42"	2
UTA-80158-M	T6 CMH 150w.	G12	30°	11500	15.4 lb.	13.42"	2
UTA-80158-W	T6 CMH 150w.	G12	40°	11500	15.4 lb.	13.42"	2
UTA-80158-VW	T6 CMH 150w.	G12	64°	11500	15.4 lb.	13.42"	2




Bottom view



Picture 1



Picture 2



Mounting detail

(VN) Very Narrow beam (N) Narrow beam (M) Medium beam (W) Wide beam (VW) Very Wide beam



Tango 15, 16 square surface exterior downlight 6.3" , 7.32" HP LED


IP65 ⚡⚡/EN 60598/CLASS I ⚡/V/CE/IK10



Suitable for wet locations - Vandal resistant.

A range of square surface mounted exterior downlight luminaires. The luminaires are suitable for indoor and outdoor applications for use in residential, shopping and public areas as surface ceiling downlights. The luminaires have features such as long life, limited maintenance and constant lifetime performance.

The luminaire is rated as class I with the high power LED integral driver. Low copper content die-cast aluminium housing with a chemical chromated protection before powder coating, ensuring high corrosion resistance. Stainless steel screws. Power is provided to the luminaire through water tight single cable gland. Durable silicone rubber gasket and clear toughened glass.




Product Family





UTA-80411-N




Tango 15 square surface downlight 6.3" HP LED

Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UTA-80411-N-W27	18 LED	1826 lm	2700K	30	14°	8.6 lb.	•
UTA-80411-N-W30	18 LED	1943 lm	3000K	30	14°	8.6 lb.	•
UTA-80411-N-W40	18 LED	1917 lm	4000K	30	14°	8.6 lb.	•
UTA-80411-M-W27	18 LED	1781 lm	2700K	30	24°	8.6 lb.	•
UTA-80411-M-W30	18 LED	1895 lm	3000K	30	24°	8.6 lb.	•
UTA-80411-M-W40	18 LED	2072 lm	4000K	30	24°	8.6 lb.	•
UTA-80411-W-W27	18 LED	1712 lm	2700K	30	40°	8.6 lb.	•
UTA-80411-W-W30	18 LED	1822 lm	3000K	30	40°	8.6 lb.	•
UTA-80411-W-W40	18 LED	1933 lm	4000K	30	40°	8.6 lb.	•




UTA-80431-W




Tango 16 square surface downlight 7.32" HP LED


Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UTA-80431-N-W27	24 LED	2392 lm	2700K	40	14°	9.9 lb.	•
UTA-80431-N-W30	24 LED	2545 lm	3000K	40	14°	9.9 lb.	•
UTA-80431-N-W40	24 LED	2750 lm	4000K	40	14°	9.9 lb.	•
UTA-80431-M-W27	24 LED	2415 lm	2700K	40	24°	9.9 lb.	•
UTA-80431-M-W30	24 LED	2570 lm	3000K	40	24°	9.9 lb.	•
UTA-80431-M-W40	24 LED	2568 lm	4000K	40	24°	9.9 lb.	•
UTA-80431-W-W27	24 LED	2295 lm	2700K	40	40°	9.9 lb.	•
UTA-80431-W-W30	24 LED	2442 lm	3000K	40	40°	9.9 lb.	•
UTA-80431-W-W40	24 LED	2488 lm	4000K	40	40°	9.9 lb.	•




Bottom view




Mounting detail




(N) Narrow beam




(M) Medium beam




(W) Wide beam




(N), (M), (W) beam in 3000K



(N), (M), (W) beam in 4000K



Bottom view



Mounting detail