





Tango 17, 18 pendant cylindrical luminaires dia. 6.3", 7.32"

IP65   /EN 60598/CLASS I  //CE/IK10




Suitable for wet locations

A range of cylindrical pendant mounted exterior down-light luminaires. Developed for all areas of interior and exterior lighting using a variety of different lamp options. These include energy saving compact fluorescent and metal halide lamps.

Low copper content die-cast aluminum housing and aluminum bottom frame with integral anti-glare baffles. Stainless steel screws and suspension kit. Durable silicone rubber gasket and clear toughened glass. Single cable entry. Housing is treated with a chemical chromated protection before powder coating, ensuring high corrosion resistance. Integral control gear. Anodized high purity aluminum reflector. Suspension height fully adjustable.

***Contact factory for LED ridged stem options**






Product Family





UTA-95204-N




Tango 17 pendant cylindrical dia 6.3"


Model No.	Lamp	Holder	Beam	Lumen	Weight	(H) Height	Picture
UTA-95201	CFQ 18w.	G24q-2	88°	1075	4.1 lb.	8.07"	1
UTA-95202-VN	T6 CMH 39w.	G12	6°	2720	7.7 lb.	9.76"	1
UTA-95202-N	T6 CMH 39w.	G12	12°	2720	7.7 lb.	9.76"	1
UTA-95202-M	T6 CMH 39w.	G12	26°	2720	7.7 lb.	9.76"	1
UTA-95202-W	T6 CMH 39w.	G12	35°	2720	7.7 lb.	9.76"	1
UTA-95202-VW	T6 CMH 39w.	G12	60°	2720	7.7 lb.	9.76"	1

Tango 18 pendant cylindrical dia. 7.32"


Model No.	Lamp	Holder	Beam	Lumen	Weight	(H) Height	Picture
UTA-95211	CFQ 26w./CFTR 32/42w.	Gx24q-3/4	64°/74°/79°	1550/2040/2720	6.3 lb.	9.45"	2
UTA-95212	PMH-ED17 70w.	MED	67°	4000	12.3 lb.	14.85"	3
UTA-95213	PMH-ED17 100w.	MED	67°	6500	12.3 lb.	14.85"	3
UTA-95214	HPS-ED 70w.	MED	79°	5450	12.3 lb.	14.85"	3
UTA-95215	HPS-ED 100w.	MED	79°	8550	12.3 lb.	14.85"	3
UTA-95216-VN	T6 CMH 70w.	G12	6°	5600	13.0 lb.	12.68"	3
UTA-95216-N	T6 CMH 70w.	G12	12°	5600	13.0 lb.	12.68"	3
UTA-95216-M	T6 CMH 70w.	G12	26°	5600	13.0 lb.	12.68"	3
UTA-95216-W	T6 CMH 70w.	G12	35°	5600	13.0 lb.	12.68"	3
UTA-95216-VW	T6 CMH 70w.	G12	60°	5600	13.0 lb.	12.68"	3
UTA-95217-VN	T6 CMH 100w.	G12	10°	7600	13.0 lb.	12.68"	3
UTA-95217-N	T6 CMH 100w.	G12	12°	7600	13.0 lb.	12.68"	3
UTA-95217-M	T6 CMH 100w.	G12	30°	7600	13.0 lb.	12.68"	3
UTA-95217-W	T6 CMH 100w.	G12	40°	7600	13.0 lb.	12.68"	3
UTA-95217-VW	T6 CMH 100w.	G12	64°	7600	13.0 lb.	12.68"	3
UTA-95218-VN	T6 CMH 150w.	G12	10°	11500	13.0 lb.	12.68"	3
UTA-95218-N	T6 CMH 150w.	G12	12°	11500	13.0 lb.	12.68"	3
UTA-95218-M	T6 CMH 150w.	G12	30°	11500	13.0 lb.	12.68"	3
UTA-95218-W	T6 CMH 150w.	G12	40°	11500	13.0 lb.	12.68"	3
UTA-95218-VW	T6 CMH 150w.	G12	64°	11500	13.0 lb.	12.68"	3



Bottom view
Picture 1



Bottom view
Picture 2



Bottom view
Picture 3



Tango 19, 20 pendant square luminaires 6.3", 7.32"

IP65 ◆ ▲ ▲ /EN 60598/CLASS I ⊕ / ▽ / CE / IK10




Suitable for wet locations

A range of square pendant mounted exterior down-light luminaires. Developed for all areas of interior and exterior lighting using a variety of different lamp options, these include energy saving compact fluorescent and metal halide lamps.

Low copper content die-cast aluminum housing and aluminum bottom frame with integral anti-glare baffles. Stainless steel screws and suspension kit. Durable silicone rubber gasket and clear toughened glass. Single cable entry. Housing is treated with a chemical chromated protection before powder coating, ensuring high corrosion resistance. Integral control gear. Anodized high purity aluminum reflector. Suspension height fully adjustable.

***Contact factory for ridged stem options**






Product Family





UTA-95182-N




Tango 19 pendant square 6.3"


Model No.	Lamp	Holder	Beam	Lumen	Weight	(H) Height	Picture
UTA-95181	CFQ 18w.	G24q-2	88°	1075	4.8 lb.	8.15"	1
UTA-95182-VN	T6 CMH 39w.	G12	6°	2720	8.3 lb.	9.84"	1
UTA-95182-N	T6 CMH 39w.	G12	12°	2720	8.3 lb.	9.84"	1
UTA-95182-M	T6 CMH 39w.	G12	26°	2720	8.3 lb.	9.84"	1
UTA-95182-W	T6 CMH 39w.	G12	35°	2720	8.3 lb.	9.84"	1
UTA-95182-VW	T6 CMH 39w.	G12	60°	2720	8.3 lb.	9.84"	1

Tango 20 pendant square 7.32"


Model No.	Lamp	Holder	Beam	Lumen	Weight	(H) Height	Picture
UTA-95191	CFQ 26w./CFTR 32/42w.	Gx24q-3/4	64°/74°/79°	1550/2040/2720	8.1 lb.	9.56"	2
UTA-95192	PMH-ED17 70w.	MED	67°	4000	14.5 lb.	15.04"	3
UTA-95193	PMH-ED17 100w.	MED	67°	6500	14.5 lb.	15.04"	3
UTA-95194	HPS-ED 70w.	MED	79°	5450	14.5 lb.	15.04"	3
UTA-95195	HPS-ED 100w.	MED	79°	8550	14.5 lb.	15.04"	3
UTA-95196-VN	T6 CMH 70w.	G12	6°	5600	15.2 lb.	12.87"	3
UTA-95196-N	T6 CMH 70w.	G12	12°	5600	15.2 lb.	12.87"	3
UTA-95196-M	T6 CMH 70w.	G12	26°	5600	15.2 lb.	12.87"	3
UTA-95196-W	T6 CMH 70w.	G12	35°	5600	15.2 lb.	12.87"	3
UTA-95196-VW	T6 CMH 70w.	G12	60°	5600	15.2 lb.	12.87"	3
UTA-95197-VN	T6 CMH 100w.	G12	10°	7600	15.2 lb.	12.87"	3
UTA-95197-N	T6 CMH 100w.	G12	12°	7600	15.2 lb.	12.87"	3
UTA-95197-M	T6 CMH 100w.	G12	30°	7600	15.2 lb.	12.87"	3
UTA-95197-W	T6 CMH 100w.	G12	40°	7600	15.2 lb.	12.87"	3
UTA-95197-VW	T6 CMH 100w.	G12	64°	7600	15.2 lb.	12.87"	3
UTA-95198-VN	T6 CMH 150w.	G12	10°	11500	15.2 lb.	12.87"	3
UTA-95198-N	T6 CMH 150w.	G12	12°	11500	15.2 lb.	12.87"	3
UTA-95198-M	T6 CMH 150w.	G12	30°	11500	15.2 lb.	12.87"	3
UTA-95198-W	T6 CMH 150w.	G12	40°	11500	15.2 lb.	12.87"	3
UTA-95198-VW	T6 CMH 150w.	G12	64°	11500	15.2 lb.	12.87"	3




Bottom view
Picture 1



Bottom view
Picture 2



Bottom view
Picture 3





Tango cylindrical and square pendant downlight HP LED

IP65 ⚡⚡/EN 60598/CLASS I ⚡/▽/CE/IK10



Suitable for wet locations

A range of cylindrical and square shape pendant exterior downlight luminaires. The luminaires are suitable for indoor and outdoor applications for use in residential, shopping and public areas as a pendant downlight. The luminaires have features such as long life, limited maintenance and constant lifetime performance.

The luminaire is rated as class I with the high power LED integral driver. Low copper content die-cast aluminium housing with a chemical chromated protection before powder coating, ensuring high corrosion resistance. Stainless steel screws. Power is provided to the luminaire through water tight single cable gland. Durable silicone rubber gasket and clear toughened glass. Suspension height fully adjustable.



- 01. Black RAL 9011	- 02. Dark Grey RAL 7043	- 03. White RAL 9003	- 04. Metallic Silver RAL 9006	- 05. Matt Silver RAL 9006	- 06. Bronze RAL 6014

Product Family

P.261 Tango 1,2 up-down light	P.263 Tango 7,8 up-down light	P.265 Tango 11,12 square up-down light	P.267 Tango 9,10 square up-down light

P.269 Tango 3,4 down light	P.271 Tango 13,14 square down light	P.273 Tango down light LED	P.279 Tango up-down light LED



P.405 Tango 5 cylindrical surface	P.411 Tango 15 square surface	P.407 Tango cylindrical LED	P.413 Tango square LED

P.561 Tango 13	P.563 Tango 14	P.657 Tango 17,18	P.659 Tango 19,20


P.661 Tango LED	P.661 Tango LED



UTA-95351-N



UTA-95361-M



Tango cylindrical pendant downlight dia. 6.3" HP LED



Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UTA-95351-N-W27	18 LED	1826 lm	2700K	30	14°	7.5 lb.	•
UTA-95351-N-W30	18 LED	1917 lm	3000K	30	14°	7.5 lb.	•
UTA-95351-N-W40	18 LED	1943 lm	4000K	30	14°	7.5 lb.	•
UTA-95351-M-W27	18 LED	1781 lm	2700K	30	24°	7.5 lb.	•
UTA-95351-M-W30	18 LED	1895 lm	3000K	30	24°	7.5 lb.	•
UTA-95351-M-W40	18 LED	2072 lm	4000K	30	24°	7.5 lb.	•
UTA-95351-W-W27	18 LED	1712 lm	2700K	30	40°	7.5 lb.	•
UTA-95351-W-W30	18 LED	1822 lm	3000K	30	40°	7.5 lb.	•
UTA-95351-W-W40	18 LED	1933 lm	4000K	30	40°	7.5 lb.	•

*Contact factory for dimming options


Tango square pendant downlight 6.3" HP LED

Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UTA-95361-N-W27	18 LED	1826 lm	2700K	30	14°	10.1 lb.	•
UTA-95361-N-W30	18 LED	1917 lm	3000K	30	14°	10.1 lb.	•
UTA-95361-N-W40	18 LED	1943 lm	4000K	30	14°	10.1 lb.	•
UTA-95361-M-W27	18 LED	1781 lm	2700K	30	24°	10.1 lb.	•
UTA-95361-M-W30	18 LED	1895 lm	3000K	30	24°	10.1 lb.	•
UTA-95361-M-W40	18 LED	2072 lm	4000K	30	24°	10.1 lb.	•
UTA-95361-W-W27	18 LED	1712 lm	2700K	30	40°	10.1 lb.	•
UTA-95361-W-W30	18 LED	1822 lm	3000K	30	40°	10.1 lb.	•
UTA-95361-W-W40	18 LED	1933 lm	4000K	30	40°	10.1 lb.	•


*Contact factory for dimming options




(N) Narrow beam



(M) Medium beam




(W) Wide beam




(N), (M), (W) beam in 3000K



(N), (M), (W) beam in 4000K




Bottom view




Mounting detail



UTA-95371-N



UTA-95381-W



Tango cylindrical pendant downlight dia. 7.32" HP LED


Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UTA-95371-N-W27	24 LED	2392 lm	2700K	40	14°	8.1 lb.	•
UTA-95371-N-W30	24 LED	2545 lm	3000K	40	14°	8.1 lb.	•
UTA-95371-N-W40	24 LED	2750 lm	4000K	40	14°	8.1 lb.	•
UTA-95371-M-W27	24 LED	2415 lm	2700K	40	25°	8.1 lb.	•
UTA-95371-M-W30	24 LED	2570 lm	3000K	40	25°	8.1 lb.	•
UTA-95371-M-W40	24 LED	2568 lm	4000K	40	25°	8.1 lb.	•
UTA-95371-W-W27	24 LED	2295 lm	2700K	40	40°	8.1 lb.	•
UTA-95371-W-W30	24 LED	2442 lm	3000K	40	40°	8.1 lb.	•
UTA-95371-W-W40	24 LED	2488 lm	4000K	40	40°	8.1 lb.	•

*Contact factory for dimming options


Tango square pendant downlight 7.32" HP LED

Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UTA-95381-N-W27	24 LED	2392 lm	2700K	40	14°	11.2 lb.	•
UTA-95381-N-W30	24 LED	2545 lm	3000K	40	14°	11.2 lb.	•
UTA-95381-N-W40	24 LED	2750 lm	4000K	40	14°	11.2 lb.	•
UTA-95381-M-W27	24 LED	2415 lm	2700K	40	25°	11.2 lb.	•
UTA-95381-M-W30	24 LED	2570 lm	3000K	40	25°	11.2 lb.	•
UTA-95381-M-W40	24 LED	2568 lm	4000K	40	25°	11.2 lb.	•
UTA-95381-W-W27	24 LED	2295 lm	2700K	40	40°	11.2 lb.	•
UTA-95381-W-W30	24 LED	2442 lm	3000K	40	40°	11.2 lb.	•
UTA-95381-W-W40	24 LED	2488 lm	4000K	40	40°	11.2 lb.	•


*Contact factory for dimming options




Bottom view




Mounting detail




(N) Narrow beam




(M) Medium beam




(W) Wide beam



Bottom view




(N), (M), (W) beam in 3000K



(N), (M), (W) beam in 4000K



UTA-95315-N







Bottom view


Tango cylindrical dia. 6.3" LED.

Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UTA-95315-N-W27	9 LED	817 lm	2700K	17	9°	7.0 lb.	•
UTA-95315-N-W30	9 LED	821 lm	3000K	17	9°	7.0 lb.	•
UTA-95315-N-W40	9 LED	939 lm	4000K	17	9°	7.0 lb.	•
UTA-95315-M-W27	9 LED	716 lm	2700K	17	13°	7.0 lb.	•
UTA-95315-M-W30	9 LED	720 lm	3000K	17	13°	7.0 lb.	•
UTA-95315-M-W40	9 LED	823 lm	4000K	17	13°	7.0 lb.	•
UTA-95315-W-W27	9 LED	751 lm	2700K	17	23°	7.0 lb.	•
UTA-95315-W-W30	9 LED	755 lm	3000K	17	23°	7.0 lb.	•
UTA-95315-W-W40	9 LED	863 lm	4000K	17	23°	7.0 lb.	•
UTA-95315-W-W27	9 LED	776 lm	2700K	17	32°	7.0 lb.	•
UTA-95315-W-W30	9 LED	780 lm	3000K	17	32°	7.0 lb.	•
UTA-95315-W-W40	9 LED	892 lm	4000K	17	32°	7.0 lb.	•

*Contact factory for dimming options



UTA-95325-N







Bottom view

Tango square 6.3" LED.

Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UTA-95325-N-W27	9 LED	817 lm	2700K	17	9°	7.7 lb.	•
UTA-95325-N-W30	9 LED	821 lm	3000K	17	9°	7.7 lb.	•
UTA-95325-N-W40	9 LED	939 lm	4000K	17	9°	7.7 lb.	•
UTA-95325-M-W27	9 LED	716 lm	2700K	17	13°	7.7 lb.	•
UTA-95325-M-W30	9 LED	720 lm	3000K	17	13°	7.7 lb.	•
UTA-95325-M-W40	9 LED	823 lm	4000K	17	13°	7.7 lb.	•
UTA-95325-W-W27	9 LED	751 lm	2700K	17	23°	7.7 lb.	•
UTA-95325-W-W30	9 LED	755 lm	3000K	17	23°	7.7 lb.	•
UTA-95325-W-W40	9 LED	863 lm	4000K	17	23°	7.7 lb.	•
UTA-95325-W-W27	9 LED	776 lm	2700K	17	32°	7.7 lb.	•
UTA-95325-W-W30	9 LED	780 lm	3000K	17	32°	7.7 lb.	•
UTA-95325-W-W40	9 LED	892 lm	4000K	17	32°	7.7 lb.	•

*Contact factory for dimming options






Tango cylindrical and square pendant downlight LED




(N), (M), (W) beam in 3000K



(N), (M), (W) beam in 4000K



(N), (M), (W) beam in 3000K



(N), (M), (W) beam in 4000K