

IP65: Suitable for Wet Locations

IK10: Impact Resistant (Vandal Resistant)

LUMINAIRE SPECIFICATION

Tel: 503-645-0500 Fax: 503-645-8100 7144 NW Progress Ct Hillsboro, Oregon 97124

www.ligmanlightingusa.com

UTA-30872

Tango 10 square wall up-down light

Wall luminaires with a variety of reflectors and lamps with up and downward light distributions. Designed to illuminate the wall surface and for light accents on vertical surfaces.

Low copper content die-cast aluminum housing and aluminum frame with integral anti-glare baffles. Stainless steel screws. Durable silicone rubber gasket and clear toughened glass. Single cable entry. Housing is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral electronic control gear. Anodized high purity aluminum reflector.

For horizontally mounted single lamp configurations a one piece multi directional anodized high purity aluminum reflector is used for up and down light distribution. Two lamp configurations use individual reflectors for up and down light distributions. Mounting plate for 3" and 4" junction box is provided with the fixture.

Physical Data Length: 11.57" Height: 10.51"

Weight: 17.6 lbs Lamp

□ T6 CMH 100w #==

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)



□ 120V □ 277V

11.57"-

Mounting detail

10.51"

Ø0.28"

8.07"

Top view

-7.32"-

Bottom view

□ Other _



☐ F - Frosted Lens

□ C - Clear Lens

Color (Please Specify)

□ 01-Black - RAL 9011 □ 03-White - RAL 9003 □ 02- Dark Grey - RAL 7043 □ 04 - Metallic Silver - RAL 9006

□ 05-Matt Silver - RAL 9006

□ 07- Custom - RAL

□ 06-Bronze - RAL 6014











Light Blade Color











☐ R - Red Light


☐ B - Blue Light


☐ Y - Yellow Light

DATE: __


☐ G - Green Light

☐ W - White Light





□ HGT- Specify Custom Height _____ft







PROJECT:

QUANTITY:

NOTE:

