

IP55 : Suitable for Wet Locations

IK08 : Impact Resistant (Vandal Resistant)

UER-30963

Euroman wall light

A decorative wall lantern with excellent downward symmetrical light distribution. Developed to compliment the Euroman post top and street lanterns. Designed for lighting of entrances, footpaths and car parks.

Low copper content die-cast aluminum housing with high corrosion resistance. Stainless steel screws. Durable silicone rubber gasket and clear or opal impact resistant UV stabilized polycarbonate diffuser. Housing is treated with a chemical chromated protection before powder coating, ensuring high corrosion resistance. Integral control gear. Anodized high purity aluminum reflector with the clear diffuser option.

Physical Data

Length: 36.89"

Height: 38.74"

Weight: 31.0 lbs

Lamp

☐ PMH-ED17 70w

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)

Voltage (Please Specify)

☐ 120V
☐ 277V
☐ Other _____

Options (Please Specify)

Diffuser



☐ C - Clear



☐ O - Opal

Top Style








☐ 1 - Dome



☐ 2 - Flat

Color (Please Specify)

☐ 01-Black - RAL 9011
☐ 03-White - RAL 9003
☐ 05-Matt Silver - RAL 9006
☐ 06-Bronze - RAL 6014
☐ 02- Dark Grey - RAL 7043
☐ 04 - Metallic Silver - RAL 9006
☐ 07- Custom - RAL _____



Ordering Example : UER - 30963 - PMH-70w - 120v - Options

PROJECT: _____ DATE: _____

TYPE: _____ QUANTITY: _____ NOTE: _____

Ligman Lighting USA reserves the right to change specifications without prior notice, please contact factory for latest information.
Due to the continual improvements in LED technology data and components may change without notice.