



# LUMINAIRE SPECIFICATION


Head Office: Tel: 503-645-0500 7144 NW Progress Ct Fax: 503-645-8100 Hillsboro, Oregon 97124 www.ligmanlightingusa.com

# IP55 : Suitable for Wet Locations IK07 : Impact Resistant (Vandal Resistant)









Mounting detail

# ULH-31152 Mini Lightsoft square wall

# Mini Lightsoft square wall light

A decorative range of cylindrical and square shape bollards with a symmetrical light distribution available in two standard heights. Developed to compliment the Lightsoft bollard and Mini Lightsoft wall light. Designed for lighting of entrances and residential areas by providing wide spread ground illumination on driveways, pathways, squares. The innovative reflector technology of the Mini Lightsoft bollard guarantees a high degree of efficiency and optimal visual comfort while fulfilling the dark sky criteria. Vandal resistant extruded aluminum and low copper content die cast housing with high corrosion resistance. Stainless steel screws. Durable silicone rubber gasket and clear impact resistant UV stabilized polycarbonate diffuser. Housing is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral control gear. Anodized high purity aluminum reflector.

## Physical Data

Length: 4.02" Height: 12.17" Weight: 6.1 lbs

#### Lamp

🗆 T4 CMH 20w 🖽 🖿

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)

## Voltage (Please Specify)

- □ 120V
- 🗆 277V
- Other

#### Color (Please Specify)

- □ 01-Black RAL 9011 □ 03-White - RAL 9003 □ 05-Matt Silver - RAL 9006 □ 06-Bronze - RAL 6014
- □ 02- Dark Grey RAL 7043
- 🗆 04 Metallic Śilver RAL 9006
- O7- Custom RAL \_\_\_\_\_\_



Top Style



#### 🗆 F - Flat



## Ordering Example : ULH - 31152 - T4 CMH-20w - 120v - Options

