


LUMINAIRE SPECIFICATION


Head Office: Tel: 503-645-0500 7144 NW Progress Ct Fax: 503-645-8100 Hillsboro, Oregon 97124 www.ligmanlightingusa.com

IP55: Suitable for Wet Locations

IK07: Impact Resistant (Vandal Resistant)









Mounting detail

UDU-30786

Duomo wall light

A decorative cylindrical shape wall lantern with symmetrical light distribution. Developed to compliment the Duomo bollard and Duomo pillar light. Designed for lighting of entrances, footpaths and car parks.

Low copper content die-cast aluminum housing with high corrosion resistance. Stainless steel screws. Durable silicone rubber gasket and opal glass diffuser. Housing is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral control gear.

Physical Data

Length: 6.3" Height: 19.06" Weight: 18.0 lbs

Lamp

□ HPS-ED17 70w **■**

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)

Voltage (Please Specify)

- □ 120V
- □ 277V
- □ Other

Options (Please Specify)

Color (Please Specify)

- □ 01-Black RAL 9011 □ 03-White - RAL 9003
 - □ 07- Custom RAL
- □ 02- Dark Grey RAL 7043 □ 04 - Metallic Silver - RAL 9006
- □ 05-Matt Silver RAL 9006
- □ 06-Bronze RAL 6014

01	
٠.	











Top Style





□ 1 - Dome

□ 2 - Flat

□ EMR- Remote Battery Pack



Ordering Example: UDU - 30786 - HPS-70w - 120v - Options



PROJECT:

QUANTITY:

NOTE:

DATE: _

