

LUMINAIRE SPECIFICATION

Tel: 503-645-0500 7144 NW Progress Ct Fax: 503-645-8100


Hillsboro, Oregon 97124


www.ligmanlightingusa.com


IP55: Suitable for Wet Locations


IK07: Impact Resistant (Vandal Resistant)











Mounting detail

UDU-30121

Duomo small shade wall light

A small and medium size shade decorative wall lantern with symmetrical light distribution. Developed to compliment the Duomo bollard and Duomo pillar light. Designed for lighting of entrances and footpaths.

Low copper content die cast housing with high corrosion resistance. Stainless steel screws. Durable silicone rubber gasket and opal glass diffuser. Housing is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral control gear.

Physical Data

Length: 16.69" Height: 12.44" Weight: 7.5 lbs

Lamp

□ CFO 13w •==

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)

Voltage (Please Specify)

- □ 120V
- □ 277V
- □ Other

Options (Please Specify)

Color (Please Specify)

- □ 01-Black RAL 9011 □ 03-White - RAL 9003
- □ 02- Dark Grey RAL 7043 □ 04 - Metallic Silver - RAL 9006

□ 07- Custom - RAL

□ 05-Matt Silver - RAL 9006 □ 06-Bronze - RAL 6014













Shade Style







Top Style








□ 2 - Cone Top









PROJECT:

QUANTITY:

NOTE:

DATE: _

