LUMINAIRE SPECIFICATION

Head Office:
7144 NW Progress Ct
Hillsboro, Oregon 97124
Tel: 503-645-0500
Fax: 503-645-8100
www.ligmanlightingusa.com

IP55 : Suitable for Wet Locations
IK07 : Impact Resistant (Vandal Resistant)



UCO-30168

Columbus medium shade wall light

A small and medium size shade decorative wall lantern with symmetrical light distribution. Developed to compliment the Columbus bollard and Columbus pillar light. Designed for lighting of entrances and footpaths.
Low copper content die cast housing with high corrosion resistance. Stainless steel screws. Durable silicone rubber gasket and opal glass diffuser. Housing is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral control gear.

Physical Data

Length: 7.68″
Height: 16.77″
Weight: 18.5 lbs

Lamp

☐ HPS-ED17 70w

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)


Voltage (Please Specify)

☐ 120V
☐ 277V
☐ Other _____

Options (Please Specify)

Color (Please Specify)

☐ 01-Black - RAL 9011
☐ 02- Dark Grey - RAL 7043
☐ 03-White - RAL 9003
☐ 04 - Metallic Silver - RAL 9006
☐ 05-Matt Silver - RAL 9006
☐ 07- Custom - RAL _____
☐ 06-Bronze - RAL 6014



Shade Style



☐ 1 - Swept Shade



☐ 2 - Straight Shade


Top Style





☐ 1 - Dome



☐ 2 - Cone Top







Mounting detail

Ordering Example : UCO - 30168 - HPS-70w - 120v - Options

PROJECT: _____ DATE: _____

TYPE: _____ QUANTITY: _____ NOTE: _____

Rev: 11/13

Ligman Lighting USA reserves the right to change specifications without prior notice, please contact factory for latest information.
Due to the continual improvements in LED technology data and components may change without notice.

Intertek