

LUMINAIRE SPECIFICATION


Head Office: Tel: 503-645-0500
7144 NW Progress Ct Fax: 503-645-8100
Hillsboro, Oregon 97124
www.ligmanlightingusa.com


IP55 : Suitable for Wet Locations
IK07 : Impact Resistant (Vandal Resistant)











Mounting detail



UDU-30209

Medium Duomo sheppards crook wall light

A wall mounted medium shade decorative lantern with a symmetrical light distribution and a sheppard's crook arm bracket. Developed to compliment the Columbus sheppard's crook post top luminaire. Designed for various applications including car parks, precincts, pathways and town centers.
Low copper content die cast housing with high corrosion resistance. Stainless steel screws. Durable silicone rubber gasket and opal glass diffuser. Housing is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral control gear.

Physical Data

Length: 26.46″
Height: 31.42″
Weight: 21.7 lbs

Lamp

☐ HPS-ED17 100w

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)


Voltage (Please Specify)

☐ 120V
☐ 277V
☐ Other _____

Options (Please Specify)

Color (Please Specify)

☐ 01-Black - RAL 9011
☐ 03-White - RAL 9003
☐ 05-Matt Silver - RAL 9006
☐ 06-Bronze - RAL 6014
☐ 02- Dark Grey - RAL 7043
☐ 04 - Metallic Silver - RAL 9006
☐ 07- Custom - RAL _____



Shade Style



☐ 1 - Swept Shade



☐ 2 - Straight Shade

Top Style




☐ 1 - Dome



☐ 2 - Cone Top



☐ DS - Dark Sky Compliant (No Rings)



Ordering Example : UDU - 30209 - HPS-100w - 120v - Options

PROJECT: _____ DATE: _____

TYPE: _____ QUANTITY: _____ NOTE: _____

Ligman Lighting USA reserves the right to change specifications without prior notice, please contact factory for latest information.
Due to the continual improvements in LED technology data and components may change without notice.

Intertek