

LUMINAIRE SPECIFICATION


Tel: 503-645-0500 7144 NW Progress Ct Hillsboro, Oregon 97124

Fax: 503-645-8100 www.ligmanlightingusa.com


IP65: Suitable for Wet Locations

IK10: Impact Resistant (Vandal Resistant)













URO-80034

Robust 1 round recessed exterior downlight

A robust 1 and 2 exterior downlight using a variety of different lamp options. These include compact fluorescent lamps, mains halogen and discharge lamps. A selection of round front frames make this luminaire an attractive option for most design applications. Robust 2 offers choices of stainless steel or powder coat painted aluminum front frame. Easy to install and relamp. This luminaires is suited for interior and exterior lighting. The Robust 1 and 2 are ball proof and suitable for sports facilities. Low copper content die-cast aluminum housing with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Stainless steel screws. Durable silicone rubber gasket and clear toughened glass. Power is provided to the luminaire through a watertight cable gland and 4ft of Outdoor Submersible #18/3 SOOW 600V power cable.

Remote control gear box is included for the luminaires using lamp sources from 70w. to 150w.

Physical Data

Diameter: 9.45"

Weight: 12.3 lbs

Lamp

□ PMH-ED17 70w

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)

Voltage (Please Specify)

- □ 120V
- □ 277V
- □ Other

Options (Please Specify)

Front Ring Style

□ Aluminum

Color (Please Specify)

- □ 01-Black RAL 9011
- □ 03-White RAL 9003
- □ 05-Matt Silver RAL 9006
- □ 06-Bronze RAL 6014













□ 02- Dark Grey - RAL 7043

□ 07- Custom - RAL

□ 04 - Metallic Silver - RAL 9006

Lens

- ☐ F Frosted Lens
- □ C Clear Lens
- □ Rough in Ceiling Tray
- □ Concrete Pour Box



Ordering Example: URO - 80034 - PMH- 70w - N - 120v - Options



PROJECT:

QUANTITY:

NOTE:

DATE: __

