LUMINAIRE SPECIFICATION

Head Office:
7144 NW Progress Ct
Hillsboro, Oregon 97124
Tel: 503-645-0500
Fax: 503-645-8100
www.ligmanlightingusa.com


IP65 : Suitable for Wet Locations
IK10 : Impact Resistant (Vandal Resistant)




URO-80066


Robust 2 round recessed exterior downlight


A robust 1 and 2 exterior downlight using a variety of different lamp options. These include compact fluorescent lamps, mains halogen and discharge lamps. A selection of round front frames make this luminaire an attractive option for most design applications. Robust 2 offers choices of stainless steel or powder coat painted aluminum front frame. Easy to install and relamp. This luminaires is suited for interior and exterior lighting. The Robust 1 and 2 are ball proof and suitable for sports facilities.
Low copper content die-cast aluminum housing with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Stainless steel screws. Durable silicone rubber gasket and clear toughened glass. Power is provided to the luminaire through a watertight cable gland and 4ft of Outdoor Submersible #18/3 SOOW 600V power cable.
Remote control gear box is included for the luminaires using lamp sources from 70w. to 150w.





Option (RT - 8.4) Rough in ceiling tray for 8.42″





Included: Remote box IP65
With Plastic Glands
Dimension: W4″xL10″xH3″
(Stainless Steel Glands Optional)
A80291



Physical Data

Diameter: 9.45″
Weight: 13.4 lbs

Lamp

☐ HPS-ED17 70w

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)

Voltage (Please Specify)

☐ 120V
☐ 277V
☐ Other _____


Options (Please Specify)

Front Ring Style

☐ Stainless Steel
☐ Aluminum


Color (Please Specify For Aluminum Front Ring Only)

☐ 01-Black - RAL 9011
☐ 02- Dark Grey - RAL 7043
☐ 03-White - RAL 9003
☐ 04 - Metallic Silver - RAL 9006
☐ 05-Matt Silver - RAL 9006
☐ 07- Custom - RAL _____
☐ 06-Bronze - RAL 6014



Lens

☐ F - Frosted Lens
☐ C - Clear Lens
☐ Rough in Ceiling Tray
☐ Concrete Pour Box





Ordering Example : URO - 80066 - HPS-70w - 120v - Options

PROJECT: _____ DATE: _____

TYPE: _____ QUANTITY: _____ NOTE: _____

Rev: 11/13

Ligman Lighting USA reserves the right to change specifications without prior notice, please contact factory for latest information.
Due to the continual improvements in LED technology data and components may change without notice.

Intertek