



LUMINAIRE SPECIFICATION


Head Office: Tel: 503-645-0500
7144 NW Progress Ct Fax: 503-645-8100
Hillsboro, Oregon 97124
www.ligmanlightingusa.com

IP65 : Suitable for Wet Locations
IK10 : Impact Resistant (Vandal Resistant)











URO-80161

Robust 3 square recessed exterior downlight

Robust 3 is an exterior downlight using a variety of different lamp options. These include compact fluorescent lamps, mains halogen and discharge lamps with square front frames. Easy to install and relamp. This luminaire is suited for interior and exterior lighting. The Robust 3 is ball proof and suitable for sports facilities. Low copper content die-cast aluminum housing with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Stainless steel screws. Durable silicone rubber gasket and clear toughened glass. Power is provided to the luminaire through a watertight cable gland and 4ft of Outdoor Submersible #18/3 SOOW 600V power cable.

 $\hfill\Box$ 02- Dark Grey - RAL 7043

□ 07- Custom - RAL

□ 04 - Metallic Silver - RAL 9006

Physical Data Trim: 9.45" Weight: 5.7 lbs

Lamp

□ PAR-38 HAL 120w •

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)

Voltage (Please Specify)

- □ 120V
- □ 277V
- □ Other

Options (Please Specify)

Front Ring Style

□ Aluminum

Color (Please Specify)

- □ 01-Black RAL 9011
- □ 03-White RAL 9003
- □ 05-Matt Silver RAL 9006
- □ 06-Bronze RAL 6014
 - 03 04 05

01 Lens

- ☐ F Frosted Lens
- □ C Clear Lens
- Rough in Ceiling Tray
- ☐ Concrete Pour Box



Ordering Example: URO - 80161 - PAR-120w - 120v - Options



PROJECT:

QUANTITY:

NOTE:

DATE:

