


# **LUMINAIRE SPECIFICATION**


Tel: 503-645-0500 7144 NW Progress Ct Fax: 503-645-8100 Hillsboro, Oregon 97124 www.ligmanlightingusa.com

IP65: Suitable for Wet Locations IK10: Impact Resistant (Vandal Resistant)



# 9.45"







## URO-80164

# Robust 3 round recessed exterior downlight

Robust 3 is an exterior downlight using a variety of different lamp options. These include compact fluorescent lamps, mains halogen and discharge lamps with square front frames. Easy to install and relamp. This luminaire is suited for interior and exterior lighting. The Robust 3 is ball proof and suitable for sports facilities. Low copper content die-cast aluminum housing with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Stainless steel screws. Durable silicone rubber gasket and clear toughened glass. Power is provided to the luminaire through a watertight cable gland and 4ft of Outdoor Submersible #18/3 SOOW 600V power cable.

**Physical Data** Trim: 9.45" Weight: 12.5 lbs

### Lamp

□ PMH-ED17 70w **■** 

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)

### Voltage (Please Specify)

- □ 120V
- □ 277V
- □ Other \_

### Options (Please Specify)

Front Ring Style

□ Aluminum

### Color (Please Specify)

- □ 01-Black RAL 9011
- □ 03-White RAL 9003
- □ 05-Matt Silver RAL 9006 □ 07- Custom - RAL □ 06-Bronze - RAI 6014









□ 02- Dark Grev - RAL 7043

□ 04 - Metallic Silver - RAL 9006

### Lens

- ☐ F Frosted Lens
- □ C Clear Lens
- □ Rough in Ceiling Tray
- □ Concrete Pour Box



Ordering Example: URO - 80164 - PMH-70w - 120v - Options



PROJECT:

QUANTITY:

NOTE:

DATE: \_

