LUMINAIRE SPECIFICATION

Head Office:
7144 NW Progress Ct
Hillsboro, Oregon 97124
Tel: 503-645-0500
Fax: 503-645-8100
www.ligmanlightingusa.com

IP65 : Suitable for Wet Locations
IK10 : Impact Resistant (Vandal Resistant)



URO-80166

Robust 3 round recessed exterior downlight

Robust 3 is an exterior downlight using a variety of different lamp options. These include compact fluorescent lamps, mains halogen and discharge lamps with square front frames. Easy to install and relamp. This luminaire is suited for interior and exterior lighting. The Robust 3 is ball proof and suitable for sports facilities.
Low copper content die-cast aluminum housing with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Stainless steel screws. Durable silicone rubber gasket and clear toughened glass. Power is provided to the luminaire through a watertight cable gland and 4ft of Outdoor Submersible #18/3 SOOW 600V power cable.

Physical Data


Trim: 9.45″


Weight: 12.5 lbs

Lamp

☐ HPS-ED17 70w

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)





Option (RT - 8.4) Rough in ceiling tray for 8.42″

Voltage (Please Specify)

☐ 120V
☐ 277V
☐ Other _____


Options (Please Specify)


Front Ring Style

☐ Aluminum

Color (Please Specify)


☐ 01-Black - RAL 9011
☐ 02- Dark Grey - RAL 7043
☐ 03-White - RAL 9003
☐ 04 - Metallic Silver - RAL 9006
☐ 05-Matt Silver - RAL 9006
☐ 07- Custom - RAL _____
☐ 06-Bronze - RAL 6014






Lens

☐ F - Frosted Lens
☐ C - Clear Lens
☐ Rough in Ceiling Tray
☐ Concrete Pour Box





Included: Remote box IP65
With Plastic Glands
Dimension: W4″xL10″xH3″
(Stainless Steel Glands Optional)
A80291

Ordering Example : URO - 80166 - HPS-70w - 120v - Options

PROJECT: _____ DATE: _____

TYPE: _____ QUANTITY: _____ NOTE: _____

Ligman Lighting USA reserves the right to change specifications without prior notice, please contact factory for latest information.
Due to the continual improvements in LED technology data and components may change without notice.