
LUMINAIRE SPECIFICATION

Head Office:
7144 NW Progress Ct
Hillsboro, Oregon 97124
Tel: 503-645-0500
Fax: 503-645-8100
www.ligmanlightingusa.com

IP65 : Suitable for Wet Locations
IK10 : Impact Resistant (Vandal Resistant)




UTA-80153


Tango 16 square surface exterior downlight

A range of cylindrical surface mounted exterior downlight luminaires. Developed for interior and exterior lighting using a variety of different lamp options. These include compact fluorescent lamps, and discharge lamps.
Low copper content die-cast aluminum housing and aluminum bottom frame with integral anti-glare baffles. Stainless steel screws. Durable silicone rubber gasket and clear toughened glass. Single cable entry. Housing is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral control gear. Anodized high purity aluminum reflector.


Physical Data

Length: 6.3″
Height: 15.63″
Weight: 15.4 lbs





Bottom view



Mounting detail

Lamp

☐ PMH-ED17 100w


(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)

Voltage (Please Specify)

☐ 120V
☐ 277V
☐ Other _____

Color (Please Specify)


☐ 01-Black - RAL 9011
☐ 02- Dark Grey - RAL 7043
☐ 03-White - RAL 9003
☐ 04 - Metallic Silver - RAL 9006
☐ 05-Matt Silver - RAL 9006
☐ 07- Custom - RAL _____
☐ 06-Bronze - RAL 6014



Lens

☐ F - Frosted Lens


☐ C - Clear Lens



☐ SCE - Surface Conduit Entry Box - ☐ 1/2″ Conduit ☐ 3/4″ Conduit

☐ Mounting Ring

☐ HGT - Specify Custom Height _____ft





Ordering Example : UTA - 80153 - PMH-100w - 120v - Options

PROJECT: _____ DATE: _____

TYPE: _____ QUANTITY: _____ NOTE: _____

Ligman Lighting USA reserves the right to change specifications without prior notice, please contact factory for latest information.
Due to the continual improvements in LED technology data and components may change without notice.