

LUMINAIRE SPECIFICATION


Head Office: Tel: 503-645-0500 7144 NW Progress Ct Fax: 503-645-8100


Hillsboro, Oregon 97124 www.ligmanlightingusa.com

IP65: Suitable for Wet Locations IK08: Impact Resistant (Vandal Resistant)













Mounting detail



UMS-91121-SFMB

Mustang 5 small surface high bay luminaire type II

Small and medium size rectangular shape wall mounted area light with cut-off light distribution for metal halide lamps high pressure sodium 70-400w. A high quality reflector design creates a broad light distribution. The luminaires are suitable for downward light distribution with adjustable mounting bracket. Designed for lighting footpaths, car parks, building facades, under canopies and roads.

Power is provided through a single PG11 watertight cable gland and 4ft of Outdoor Submersible #18/3 SOOW 600V power cable. Low copper content corrosion resistant die-cast aluminum frame and body. Stainless steel screws. Durable silicone rubber gasket and impact resistant toughened glass diffuser with hinged aluminum frame for in-position lamp replacement. The luminaire is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral electronic control gear. Anodized high purity 95% reflective aluminum reflector.

Physical Data

Length: 17.72" Height: 5.91" Weight: 17.4 lbs

Lamp

□ PMH-ED17 50w **■**

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)

Voltage (Please Specify)

- □ 120V
- □ 277V
- □ Other

Options (Please Specify)

Color (Please Specify)

- □ 01-Black RAL 9011
- □ 02- Dark Grey RAL 7043
- □ 03-White RAL 9003
- □ 04 Metallic Śilver RAL 9006 □ 07- Custom - RAL
- □ 05-Matt Silver RAL 9006 □ 06-Bronze - RAL 6014













DATE: _

Lens

- ☐ F Frosted Lens
- □ C Clear Lens



Ordering Example: UMS - 91121-SFMB - PMH-50w - 120v - Options



PROJECT:

QUANTITY:

NOTE:

