


LUMINAIRE SPECIFICATION


Head Office: Tel: 503-645-0500 7144 NW Progress Ct Fax: 503-645-8100 Hillsboro, Oregon 97124 www.ligmanlightingusa.com

IP65 : Suitable for Wet Locations IK08 : Impact Resistant (Vandal Resistant)









Adjustable



Ordering Example : UMS - 91123-SAMB - PMH-100w - 120v - Options

PROJECT:

Rev: 11/13

distribution for metal halide lamps high pressure sodium 70-400w. A high quality reflector design creates a broad light distribution. The luminaires are suitable for downward light distribution with adjustable mounting bracket. Designed for lighting footpaths, car parks, building facades, under canopies and roads. Power is provided through a single PG11 watertight cable gland and 4ft of Outdoor Submersible #18/3 SOOW 600V power cable. Low copper content corrosion resistant

UMS-91123-SAMB

die-cast aluminum frame and body. Stainless steel screws. Durable silicone rubber gasket and impact resistant toughened glass diffuser with hinged aluminum frame for in-position lamp replacement. The luminaire is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral electronic control gear. Anodized high purity 95% reflective aluminum reflector.

Mustang 7 small surface high bay luminaire type II

Small and medium size rectangular shape wall mounted area light with cut-off light

Physical Data

Length: 22.05"

Height: 5.91"

Weight: 19.6 lbs

Lamp

🗆 PMH-ED17 100w 🔍

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)

Voltage (Please Specify)

□ 120V

□ 277V

□ Other_

Options (Please Specify)

Color (Please Specify)

□ 01-Black - RAL 9011
 □ 03-White - RAL 9003
 □ 05-Matt Silver - RAL 9006
 □ 06-Bronze - RAL 6014

□ 02- Dark Grey - RAL 7043

- □ 04 Metallic Śilver RAL 9006
- 07- Custom RAL _____





□ F - Frosted Lens









 TYPE:
 QUANTITY:
 NOTE:

 Ligman Lighting USA reserves the right to change specifications without prior notice, please contact factory for latest information.
 Due to the continual improvements in LED technology data and components may change without notice.