

LUMINAIRE SPECIFICATION

Single cable entry. **Physical Data** Length: 22.05" Height: 5.91" Weight: 16.3 lbs

□ HPS-ED17 100w 🔍

Voltage (Please Specify)

Options (Please Specify)

Color (Please Specify)

Lamp

□ 120V □ 277V

□ Other


UMS-91157-SFMB

Head Office: Tel: 503-645-0500 7144 NW Progress Ct Fax: 503-645-8100 Hillsboro, Oregon 97124 www.ligmanlightingusa.com


IP54 : Suitable for Wet Locations IK07 : Impact Resistant (Vandal Resistant)







F - 17.72″ ---



Mounting detail

Due to the continual improvements in LED technology data and components may change without notice.



□ 01-Black - RAL 9011 □ 03-White - RAL 9003 D 05-Matt Silver - RAL 9006 □ 06-Bronze - RAL 6014

□ 02- Dark Grey - RAL 7043

Mustang 16 small surface high bay luminaire type II

Aluminum housing and hinged aluminum bottom frame with clear toughened glass lens. Stainless steel screws. Durable silicone rubber gasket and single PG 11 cable entry. Housing is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Anodized high purity aluminum reflector

Small and medium size rectangular shaped recessed high bay with a selection of reflector options giving a variety highly efficient of beam distributions. Designed for use with metal halide and high pressure sodium lamps 70-400w. The high quality reflector design ensures excellent light distribution. Designed for lighting of sports

facilities, warehouses, factories, and under canopy lighting.

(For More Lamp options including LED, please Consult the Catalogue,

Website or Contact The Ligman Lighting Factory)

- □ 04 Metallic Silver RAL 9006
- □ 07- Custom RAL



Lens

- □ F Frosted Lens
- C Clear Lens





Ordering Example : UMS - 91157-SFMB - HPS-100w - 120v - Options





