

LUMINAIRE SPECIFICATION

Tel: 503-645-0500 7144 NW Progress Ct Fax: 503-645-8100

Hillsboro, Oregon 97124


www.ligmanlightingusa.com


IP54: Suitable for Wet Locations

IK07: Impact Resistant (Vandal Resistant)














UMS-91283-SFMB

Mustang small surface high bay luminaire type V

Small and medium size rectangular shaped recessed high bay with a selection of reflector options giving a variety highly efficient of beam distributions. Designed for use with metal halide and high pressure sodium lamps 70-400w. The high quality reflector design ensures excellent light distribution. Designed for lighting of sports facilities, warehouses, factories, and under canopy lighting.

Aluminum housing and hinged aluminum bottom frame with clear toughened glass lens. Stainless steel screws. Durable silicone rubber gasket and single PG 11 cable entry. Housing is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Anodized high purity aluminum reflector Single cable entry.

Physical Data

Length: 20.47" Height: 5.91" Weight: 16.9 lbs

Lamp

□ PMH-ED17 100w

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)

Voltage (Please Specify)

- □ 120V
- □ 277V
- □ Other

Options (Please Specify)

Color (Please Specify)

- □ 01-Black RAL 9011
- □ 02- Dark Grey RAL 7043
- □ 03-White RAL 9003
- □ 04 Metallic Silver RAL 9006
- □ 05-Matt Silver RAL 9006
- □ 07- Custom RAL
- □ 06-Bronze RAL 6014














- ☐ F Frosted Lens
- □ C Clear Lens





Ordering Example: UMS - 91283-SFMB - PMH-100w - 120v - Options



PROJECT:

QUANTITY:

NOTE:

DATE: _

