
# LUMINAIRE SPECIFICATION

Head Office:
7144 NW Progress Ct
Hillsboro, Oregon 97124
Tel: 503-645-0500
Fax: 503-645-8100
www.ligmanlightingusa.com


IP54 : Suitable for Wet Locations
IK07 : Impact Resistant (Vandal Resistant)









Top view



Bottom view



Mounting detail

# UMS-92161-MFMB

## Mustang 17 medium surface high bay luminaire type II

Small and medium size rectangular shaped recessed high bay with a selection of reflector options giving a variety highly efficient of beam distributions. Designed for use with metal halide and high pressure sodium lamps 70-400w. The high quality reflector design ensures excellent light distribution. Designed for lighting of sports facilities, warehouses, factories, and under canopy lighting.
Aluminum housing and hinged aluminum bottom frame with clear toughened glass lens. Stainless steel screws. Durable silicone rubber gasket and single PG 11 cable entry. Housing is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Anodized high purity aluminum reflector Single cable entry.

### Physical Data

Length: 24.8″
Height: 7.08″
Weight: 29.7 lbs

### Lamp

☐ PMH-T15 200w

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)


### Voltage (Please Specify)

☐ 120V
☐ 277V
☐ Other _____

### Options (Please Specify)


Color (Please Specify)

☐ 01-Black - RAL 9011
☐ 02- Dark Grey - RAL 7043
☐ 03-White - RAL 9003
☐ 04 - Metallic Silver - RAL 9006
☐ 05-Matt Silver - RAL 9006
☐ 07- Custom - RAL _____
☐ 06-Bronze - RAL 6014




Lens

☐ F - Frosted Lens
☐ C - Clear Lens






*Ordering Example : UMS - 92161-MFMB - PMH-200w - 120v - Options*

PROJECT: _____ DATE: _____

TYPE: _____ QUANTITY: _____ NOTE: _____



Ligman Lighting USA reserves the right to change specifications without prior notice, please contact factory for latest information.
Due to the continual improvements in LED technology data and components may change without notice.