

LUMINAIRE SPECIFICATION

Head Office:
7144 NW Progress Ct
Hillsboro, Oregon 97124
Tel: 503-645-0500
Fax: 503-645-8100
www.ligmanlightingusa.com

IP65 : Suitable for Wet Locations
IK08 : Impact Resistant (Vandal Resistant)







Mounting detail

UJE-10552

Jet square bollard

The Jet's square shape integrated with square column provides downlight distribution with optimal visual comfort through great glare control fulfilling dark sky criteria. Lamp choices include line voltage halogen and T4 metal halide and LED with a selection of precision reflectors for optimum beam control as well as high efficiency. Long service life and vandal resistance are the further characteristics of this compact bollard.
Developed for lighting driveways, pathways and squares.
Die-cast aluminum housing with high corrosion resistance. Stainless steel screws. Extruded aluminum column. Durable silicone rubber gasket and clear toughened glass. Housing is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral control gear.

Physical Data

Length: 11.73″
Height: 47.24″
Weight: 16.3 lbs

Lamp

☐ MR-16 FL 50w

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)


Voltage (Please Specify)

☐ 120V


Options (Please Specify)

Color (Please Specify)

☐ 01-Black - RAL 9011
☐ 02- Dark Grey - RAL 7043
☐ 03-White - RAL 9003
☐ 04 - Metallic Silver - RAL 9006
☐ 05-Matt Silver - RAL 9006
☐ 07- Custom - RAL _____
☐ 06-Bronze - RAL 6014



Mounting Accessories




☐ Anchor Bolt Kit

☐ Specify custom Bollard height_____ ft

☐ F - Frosted Lens

☐ C - Clear Lens





Ordering Example : UJE- 10552 - MR - 50w - 120v - Options

PROJECT: _____ DATE: _____

TYPE: _____ QUANTITY: _____ NOTE: _____

Rev: 11/13

Ligman Lighting USA reserves the right to change specifications without prior notice, please contact factory for latest information.
Due to the continual improvements in LED technology data and components may change without notice.

Intertek