




For installation of Aqua Underwater lighting LED.  
Model. UAQ-60001, UAQ-60011 and UAQ-60021.

## Product drawing (dimensions)

## SUITABLE FOR WET LOCATIONS




Power input conduit  
OD 20mm.(0.78")



①

(Brown)Vdc+


(Blue)Vdc-



**WARNING**

②


Cable input 36Vdc for  
AQ-60001= 350mA  
AQ-60011= 500mA  
AQ-60021= 700mA




Cable connector IP68  
Customer supply

③

④



⑤



## Notice to installer :

- 1.WIRING INSTRUCTIONS Warning : RISK OF FIRE AND ELECTRICAL SHOCK. : FIXTURE MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN ONLY>FIXTURE IS INTENDED FOR INSTALLATION IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, LOCAL AND FEDERAL CODE SPECIFICATIONS. DISCONNECT POWER BEFORE SERVICING.**
- 2.This fixture has a VOLTAGE SPECIFIC BALLAST,Check that the supply voltage is the same as the installed ballast voltage.**

**Ligman Lighting USA**

7144 NE Progress Court, Hillsboro  
Oregon, 97124, USA  
Tel : 503 645 0500 | Fax : 503 645 8100

www.ligmanlightingusa.com

UAQ-60001/15/03/17/REV.1 /PUT  
1/1

FM-TS-13-2/15-03-2561/Rev.3