

IP55 : Suitable for Wet Locations

IK08 : Impact Resistant (Vandal Resistant)



## URM-10063

### Romeo bollard

A distinct style of bollards with a symmetrical light distribution using energy saving compact fluorescent lamps as well as metal halide and high pressure sodium lamps. Designed for lighting of entrances, footpaths, squares and gardens. Extruded aluminum column. Die-cast aluminum housing with high corrosion resistance. Stainless steel screws. Durable silicone rubber gasket. Opal glass diffuser. Powder paint with high corrosion resistance with chemical chromated protection. Integral control gear.

#### Physical Data

Length: 16.22"

Height: 42.83"

Weight: 24.6 lbs

#### Lamp

☐ PMH-ED17 50w 

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)




#### Voltage (Please Specify)

☐ 120V  
☐ 277V  
☐ Other \_\_\_\_\_

#### Options (Please Specify)


Color (Please Specify)

☐ 01-Black - RAL 9011  
☐ 03-White - RAL 9003  
☐ 05-Matt Silver - RAL 9006  
☐ 06-Bronze - RAL 6014  
☐ 02- Dark Grey - RAL 7043  
☐ 04 - Metallic Silver - RAL 9006  
☐ 07- Custom - RAL \_\_\_\_\_




Mounting detail

#### Mounting Accessories



☐ Anchor Bolt Kit  
☐ Specify Custom Height \_\_\_\_\_ ft



Ordering Example : URM - 10063 - PMH - 50w - 120v - Options



Rev: 11/13

PROJECT: \_\_\_\_\_ DATE: \_\_\_\_\_

TYPE: \_\_\_\_\_ QUANTITY: \_\_\_\_\_ NOTE: \_\_\_\_\_

Ligman Lighting USA reserves the right to change specifications without prior notice, please contact factory for latest information.  
Due to the continual improvements in LED technology data and components may change without notice.

