

LUMINAIRE SPECIFICATION


Head Office: Tel: 503-645-0500 7144 NW Progress Ct Fax: 503-645-8100 Hillsboro, Oregon 97124


www.ligmanlightingusa.com

IP55 : Suitable for Wet Locations

IK08: Impact Resistant (Vandal Resistant)







URM-70061

Romeo pillar light

A distinct style of bollards with a symmetrical light distribution using energy saving compact fluorescent lamps as well as metal halide and high pressure sodium lamps. Designed for lighting of entrances, footpaths, squares and gardens. Extruded aluminum column. Die-cast aluminum housing with high corrosion resistance. Stailess steel screws. Durable silicone rubber gasket. One glass diffuser

resistance. Stainless steel screws. Durable silicone rubber gasket. Opal glass diffuser. Powder paint with high corrosion resistance with chemical chromatized protection. Integral control gear.

Physical Data

Length: 16.22" Height: 18.74" Weight: 15.4 lbs

Lamp

□ SPIRAL-CFL 23w <□

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)

Voltage (Please Specify)

- □ 120V
- □ 277V
- □ Other____

Options (Please Specify)

Color (Please Specify)

- □ 01-Black RAL 9011
- □ 03-White RAL 9003
- □ 05-Matt Silver RAL 9006
- □ 06-Bronze RAL 6014
 - AL 6014







□ 02- Dark Grey - RAL 7043

□ 07- Custom - RAL

□ 04 - Metallic Śilver - RAL 9006

Mounting Accessories



- ☐ Anchor Bolt Kit
- □ Specify Custom Height _____ft



Ordering Example: URM - 70061 - SPIRAL-CFL - 23w - 120v - Options



PROJECT:

YPE: _____ QUANTITY:

NOTE:

DATE:

