



Romeo bollard

IP55 ✱ ▲ ▲ / EN 60598 / CLASS I ⚡ / ▽ / CE / IK08




Suitable for wet locations

A distinct style of bollards with a symmetrical light distribution using energy saving compact fluorescent lamps as well as metal halide and high pressure sodium lamps. Designed for lighting of entrances, footpaths, squares and gardens.

Dark sky compliant

Extruded aluminum column. Die-cast aluminum housing with high corrosion resistance. Stainless steel screws. Durable silicone rubber gasket. Opal glass diffuser. Powder coating with high corrosion resistance with chemical chromatized protection. Integral control gear.



Product Family




P.497
bollard



P.497
pillar light

Accessories



Anchor bolt kit for installation
A10191



URM-10051

Romeo bollard

Model No.	Lamp	Holder	Lumen	Weight	(H) Height
URM-10051	CFQ 18w.	G24q-2	1075	20.7 lb.	31.85"
URM-10052	CFQ 26w./CFTR 32/42w.	Gx24q-3/4	1550/2040/2720	20.9 lb.	31.85"
URM-10053	PMH-ED17 50w.	MED	2100	22.7 lb.	31.85"
URM-10054	PMH-ED17 70w.	MED	4000	22.7 lb.	31.85"
URM-10055	HPS-ED17 50w.	MED	3600	22.2 lb.	31.85"
URM-10056	HPS-ED17 70w.	MED	5450	22.2 lb.	31.85"
URM-10061	CFQ 18w.	G24q-2	1075	24.4 lb.	42.83"
URM-10062	CFQ 26w./CFTR 32/42w.	Gx24q-3/4	1550/2040/2720	24.6 lb.	42.83"
URM-10063	PMH-ED17 50w.	MED	2100	26.2 lb.	42.83"
URM-10064	PMH-ED17 70w.	MED	4000	26.2 lb.	42.83"
URM-10065	HPS-ED17 50w.	MED	3600	25.1 lb.	42.83"
URM-10066	HPS-ED17 70w.	MED	5450	25.1 lb.	42.83"

Romeo pillar light

Model No.	Lamp	Holder	Lumen	Weight	(H) Height
URM-70061	SPIRAL-CFL 23w.	MED	1600	15.4 lb.	18.74"

