

LUMINAIRE SPECIFICATION


Head Office: Tel: 503-645-0500 7144 NW Progress Ct Fax: 503-645-8100


Hillsboro, Oregon 97124 www.ligmanlightingusa.com

IP55: Suitable for Wet Locations

IK08: Impact Resistant (Vandal Resistant)









UDU-10194

Duomo 2 bollard

A decorative bollard with a symmetrical light distribution with options of energy saving LED, compact fluorescent, metal halide and high pressure sodium lamps. Developed to compliment the Duomo range of pillar light, post top and wall light luminaires. Designed for various applications including – entrances, gardens, precincts and pathways.

Extruded aluminum column and low copper content die cast housing with high corrosion resistance. Stainless steel screws. Durable silicone rubber gasket and opal glass diffuser. Housing is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral control gear.

Physical Data

Length: 7.32"

Height: 29.84"/31.18" Weight: 20.7 lbs

Lamp

□ PMH-ED17 70w

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)

Voltage (Please Specify)

- □ 120V
- □ 277V
- □ Other

Options (Please Specify)

Color (Please Specify)

- □ 01-Black RAL 9011
- □ 03-White RAL 9003
- □ 05-Matt Silver RAL 9006
- □ 06-Bronze RAL 6014









□ 02- Dark Grey - RAL 7043

□ 04 - Metallic Silver - RAL 9006



□ 07- Custom - RAL

Top Style



□ 1 - Dome





Mounting Accessories



- □ Anchor Bolt Kit
- □ Specify Custom Height _____ft

Light Shields



180° emission







Ordering Example: UDU - 10194 - PMH - 70w - 120v - Options



PROJECT:

QUANTITY:

NOTE:

DATE: _

