




IP67 : Suitable for Wet Locations

IK10 : Impact Resistant (Vandal Resistant)



Top view



Mounting detail



## UVR-70272

### Veranda pillar light

A top range of above ground guide lights with light distribution options from one, two or four sectors. Designed for use in shopping, pedestrian and park areas with a selection of low voltage, energy saving compact fluorescent and metal halide lamps as well as LED's. Main characteristics are low glare and the limited maintenance concept when using LED's. This product has a standard 'touchable dome' ideally suited for spaces that are used by the general public. The luminaires have a high quality LED source with low energy consumption and long service life 60,000 – 80,000 Hrs.

Body and frame constructed in low copper content die-cast aluminum with high corrosion resistance. Fasteners in grade 316 stainless steel. Power is provided through a single PG11 watertight cable gland and 1.2m / 4ft of Outdoor Submersible #18/3 SOOW 600V power cable. Durable silicone rubber gasket and clear glass lens.

### Physical Data

Length: 11.96"

Height: 10.03"

Weight: 12.3 lbs

### Lamp

☐ T6 CMH 70w

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)

### Voltage (Please Specify)

- ☐ 120V  
☐ 277V  
☐ Other \_\_\_\_\_


### Options (Please Specify)

Color (Please Specify)




- ☐ 01-Black - RAL 9011 ☐ 02- Dark Grey - RAL 7043  
☐ 03-White - RAL 9003 ☐ 04 - Metallic Silver - RAL 9006  
☐ 05-Matt Silver - RAL 9006 ☐ 07- Custom - RAL \_\_\_\_\_  
☐ 06-Bronze - RAL 6014



### Mounting Accessories



☐ Anchor Bolt Kit



Ordering Example : UVR - 70272 - T6 CMH - 70w - 120v - Options

PROJECT: \_\_\_\_\_ DATE: \_\_\_\_\_

TYPE: \_\_\_\_\_ QUANTITY: \_\_\_\_\_ NOTE: \_\_\_\_\_

Ligman Lighting USA reserves the right to change specifications without prior notice, please contact factory for latest information.  
Due to the continual improvements in LED technology data and components may change without notice.