

LUMINAIRE SPECIFICATION

Head Office: Tel: 503-645-0500
7144 NW Progress Ct Fax: 503-645-8100
Hillsboro, Oregon 97124
www.ligmanlightingusa.com


IP67 : Suitable for Wet Locations


IK10: Impact Resistant (Vandal Resistant)





Top view





Mounting detail



UVR-70291

Veranda pillar light

A top range of above ground guide lights with light distribution options from one, two or four sectors. Designed for use in shopping, pedestrian and park areas with a selection of low voltage, energy saving compact fluorescent and metal halide lamps as well as LED's. Main characteristics are low glare and the limited maintenance concept when using LED's. This product has a standard 'touchable dome' ideally suited for spaces that are used by the general public. The luminaires have a high quality LED source with low energy consumption and long service life 60,000 – 80,000 Hrs.

Body and frame constructed in low copper content die-cast aluminum with high corrosion resistance. Fasteners in grade 316 stainless steel. Power is provided through a single PG11 watertight cable gland and 1.2m / 4ft of Outdoor Submersible #18/3 SOOW 600V power cable. Durable silicone rubber gasket and clear glass lens.

Physical Data

Length: 11.96" Height: 10.03" Weight: 12.8 lbs

Lamp

□ T6 CMH 39w #==

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)

Voltage (Please Specify)

- □ 120V
- □ 277V
- □ Other ____

Options (Please Specify)

Color (Please Specify)

- ☐ 01-Black RAL 9011
- □ 02- Dark Grey RAL 7043
- □ 03-White RAL 9003□ 05-Matt Silver RAL 9006
- □ 04 Metallic Silver RAL 9006□ 07 Custom RAL
- □ 06-Bronze RAL 6014













Mounting Accessories



☐ Anchor Bolt Kit



Ordering Example: UVR - 70291 - T6 CMH - 39w - 120v - Options



PROJECT:

DE. OLIANTITY

OUANTITY:

NOTE:

_ DATE: _____

