LIGMAN LIGHTING USA

IP65 : Suitable for Wet Locations
IK10 : Impact Resistant (Vandal Resistant)

UTA-20721
Tango 14 double post top

Tango post top luminaire was developed to compliment the Tango and Jet range of wall mount luminaires as well as the Jet square bollards, using energy saving compact fluorescent, metal halide and high pressure sodium lamps. This rectangular profiled luminaire mounted on a square extruded aluminum pole is available with different reflectors, downward light beam distributions and lamp options. Designed for residential and shopping areas, squares and parks. Available with a selection of integral electronic ballasts.

Low copper content die-cast aluminum housing and aluminum bottom frame with integral anti-glare baffles. Stainless steel screws. Durable silicone rubber gasket and clear toughened glass lens. Single cable entry. Housing is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral control gear. Anodized high purity aluminum reflector.

Physical Data
Length: 25.6"
Height: 9.56"
Weight: 50.2 lb

Lamp
☐ CFQ 2x26w/ CFTR 2x32/42w

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)

Voltage (Please Specify)
☐ 120V
☐ 277V
☐ Other _____

Color (Please Specify)

☐ 01-Black - RAL 9011   ☐ 02- Dark Grey - RAL 7043
☐ 03-White - RAL 9003   ☐ 04 - Metallic Silver - RAL 9006
☐ 05-Matt Silver - RAL 9006   ☐ 07- Custom - RAL _____
☐ 06-Bronze - RAL 6014

| 01 | 02 | 03 | 04 | 05 | 06 |

Lens

☐ F - Frosted Lens

☐ C - Clear Lens

☐ HGT - Specify Custom Height _____ ft

Drawing dimensions: 25.6", 9.56", 7.32"x7.32", 4.01"x4.01", 9'-10.11", 0.59"

Mounting detail: 0.86"x1.96", 6.57", 9.84", 6.57", 9.84", 4.02"x4.02", 0.59"

Ordering Example : UTA - 20721- CFQ - 2x26w - 120v - Options

PROJECT: _____   DATE: _____

TYPE: _____ QUANTITY: _____ NOTE: _____

Rev: 11/13

ETL Intertek