






Tango 2 #UTA-30385-VN T6 CMH 2X70W 6°




Tango 2 #UTA-30385-N T6 CMH 2X70W 12°




Tango 2 #UTA-30385-M T6 CMH 2X70W 26°




Tango 2 #UTA-30385-W T6 CMH 2X70W 35°




Tango 2 #UTA-30385-VW T6 CMH 2X70W 60°








Tango 1 #UTA-30403 T6 CMH 39W





Tango 2 #UTA-30384-W T6 CMH 70W



Tango 2 #UTA-30387-W T6 CMH 150W



Tango 4 #UTA-30392-10 PMH-ED17 100W



Tango 4 #UTA-30391 CFTR 42W

Tango 1, 2 cylindrical wall up-down light


IP65 ◆ ▲ ▲ /EN 60598/CLASS I Ⓢ / ▽ / CE / IK10



Suitable for wet locations


Wall luminaires with a variety of reflectors and lamps with up and downward light distributions. Designed to illuminate the wall surface and for light accents on vertical surfaces. Low copper content die-cast aluminum housing and aluminum frame with integral anti-glare baffles. Stainless steel screws. Durable silicone rubber gasket and clear toughened glass. Single cable entry. Housing is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral electronic control gear. Anodized high purity aluminum reflector.

For horizontally mounted single lamp configurations a one piece multi directional anodized high purity aluminum reflector is used for up and down light distribution. Two lamp configurations use individual reflectors for up and down light distributions. To maintain the integrity of the IP rating of this luminaire it is supplied with a specially designed SHG self sealing wiring grommet that is used when connecting to the power supply. This grommet insures that water and dust does not enter the luminaire through the knockout hole in the back of the luminaire. Consult factory for mixing reflector and lamp options.




Product Family







UTA-30404-W





Tango 1 cylindrical wall up-down light


Model No.	Lamp	Holder	Beam	Lumen	Weight	(H) Height	Picture
UTA-30401	T4 HALOGEN 150w. 120v	MINI-CAN	64°	2400	5.5 lb.	7.72"	1
UTA-30402	CFQ 2x18w.	G24q-2	88°	2x1075	12.3 lb.	16.14"	2
UTA-30403	T6 CMH 39w.	G12	54°	2720	9.4 lb.	7.72"	2
UTA-30404-VN	T6 CMH 2x39w.	G12	6°	2x2720	16.7 lb.	18.9"	2
UTA-30404-N	T6 CMH 2x39w.	G12	12°	2x2720	16.7 lb.	18.9"	2
UTA-30404-M	T6 CMH 2x39w.	G12	26°	2x2720	16.7 lb.	18.9"	2
UTA-30404-W	T6 CMH 2x39w.	G12	35°	2x2720	16.7 lb.	18.9"	2
UTA-30404-VW	T6 CMH 2x39w.	G12	60°	2x2720	16.7 lb.	18.9"	2



Top view




Bottom view





Mounting detail


Picture 1




Top view




Bottom view





Mounting detail
Picture 2



UTA-30384-W






Top view



Bottom view

Tango 2 cylindrical wall up-down light

Model No.	Lamp	Holder	Beam	Lumen	Weight	(H) Height
UTA-30381	CFQ 2x26w./JCFTR 2x32/42w.	Gx24q-3/4	79°/74°/79°	2x1550/2x2040/2x2720	14.3 lb.	18.31"
UTA-30382	PMH-ED17 2x70w.	MED	67°	2x4000	23.5 lb.	22.24"
UTA-30383	HPS-ED17 2x70w.	MED	79°	2x5450	23.5 lb.	22.24"
UTA-30384-N	T6 CMH 70w.	G12	18°	5600	13.4 lb.	10.24"
UTA-30384-W	T6 CMH 70w.	G12	59°	5600	13.4 lb.	10.24"
UTA-30385-VN	T6 CMH 2x70w.	G12	6°	2x5600	22.7 lb.	20.2"
UTA-30385-N	T6 CMH 2x70w.	G12	12°	2x5600	22.7 lb.	20.2"
UTA-30385-M	T6 CMH 2x70w.	G12	26°	2x5600	22.7 lb.	20.2"
UTA-30385-W	T6 CMH 2x70w.	G12	35°	2x5600	22.7 lb.	20.2"
UTA-30385-VW	T6 CMH 2x70w.	G12	60°	2x5600	22.7 lb.	20.2"
UTA-30386-N	T6 CMH 100w.	G12	18°	7600	14.7 lb.	10.24"
UTA-30386-W	T6 CMH 100w.	G12	59°	7600	14.7 lb.	10.24"
UTA-30387-N	T6 CMH 150w.	G12	18°	11500	14.7 lb.	10.24"
UTA-30387-W	T6 CMH 150w.	G12	59°	11500	14.7 lb.	10.24"



Mounting detail

Tango 7, 8 cylindrical wall up-down light

IP65 ◆ ▲ ▲ / EN 60598/CLASS I Ⓢ / ▽ / CE / IK10




Suitable for wet locations



Wall luminaires with a variety of reflectors and lamps with up and downward light distributions using a single lamp mounted horizontally. Designed to illuminate the wall surface and for light accents on vertical surfaces.

The upward light component consists of a sharp beam of light that is controlled by a glass prism this can be used to highlight architectural features on buildings. The light beams can be red, blue, yellow green, and white.

Low copper content die-cast aluminum housing and aluminum frame with integral anti-glare baffles. Stainless steel screws. Durable silicone rubber gasket and clear toughened glass. Single cable entry. Housing is treated with a chemical chromated protection before powder coating, ensuring high corrosion resistance. Integral electronic control gear. Anodized high purity aluminum reflector. To maintain the integrity of the IP rating of this luminaire it is supplied with a specially designed SHG self sealing wiring grommet that is used when connecting to the power supply. This grommet insures that water and dust does not enter the luminaire through the knockout hole in the back of the luminaire.




Product Family









UTA-30761-W




Tango 7 cylindrical wall up-down light

Model No.	Lamp	Holder	Beam	Lumen	Weight
UTA-30761-R	T6 CMH 39w.	G12	3.5°/32°	2720	10.8 lb.
UTA-30761-B	T6 CMH 39w.	G12	3.5°/32°	2720	10.8 lb.
UTA-30761-Y	T6 CMH 39w.	G12	3.5°/32°	2720	10.8 lb.
UTA-30761-G	T6 CMH 39w.	G12	3.5°/32°	2720	10.8 lb.
UTA-30761-W	T6 CMH 39w.	G12	3.5°/32°	2720	10.8 lb.






UTA-30771-W







Tango 8 cylindrical wall up-down light

Model No.	Lamp	Holder	Beam	Lumen	Weight
UTA-30771-R	T6 CMH 70w.	G12	3.5°/34°	5600	14.7 lb.
UTA-30771-B	T6 CMH 70w.	G12	3.5°/34°	5600	14.7 lb.
UTA-30771-Y	T6 CMH 70w.	G12	3.5°/34°	5600	14.7 lb.
UTA-30771-G	T6 CMH 70w.	G12	3.5°/34°	5600	14.7 lb.
UTA-30771-W	T6 CMH 70w.	G12	3.5°/34°	5600	14.7 lb.
UTA-30772-R	T6 CMH 100w.	G12	4°/36°	7600	16.0 lb.
UTA-30772-B	T6 CMH 100w.	G12	4°/36°	7600	16.0 lb.
UTA-30772-Y	T6 CMH 100w.	G12	4°/36°	7600	16.0 lb.
UTA-30772-G	T6 CMH 100w.	G12	4°/36°	7600	16.0 lb.
UTA-30772-W	T6 CMH 100w.	G12	4°/36°	7600	16.0 lb.
UTA-30773-R	T6 CMH 150w.	G12	4°/36°	11500	16.0 lb.
UTA-30773-B	T6 CMH 150w.	G12	4°/36°	11500	16.0 lb.
UTA-30773-Y	T6 CMH 150w.	G12	4°/36°	11500	16.0 lb.
UTA-30773-G	T6 CMH 150w.	G12	4°/36°	11500	16.0 lb.
UTA-30773-W	T6 CMH 150w.	G12	4°/36°	11500	16.0 lb.



Tango 11, 12 square wall up-down light

IP65   /EN 60598/CLASS I  //CE/IK10




Suitable for wet locations

Wall luminaires with a variety of reflectors and lamps with up and downward light distributions. Designed to illuminate the wall surface and for light accents on vertical surfaces.

Low copper content die-cast aluminum housing and aluminum frame with integral anti-glare baffles. Stainless steel screws. Durable silicone rubber gasket and clear toughened glass. Single cable entry. Housing is treated with a chemical chromated protection before powder coating, ensuring high corrosion resistance. Integral electronic control gear. Anodized high purity aluminum reflector.

For horizontally mounted single lamp configurations a one piece multi directional anodized high purity aluminum reflector is used for up and down light distribution. Two lamp configurations use individual reflectors for up and down light distributions. To maintain the integrity of the IP rating of this luminaire it is supplied with a specially designed SHG self sealing wiring grommet that is used when connecting to the power supply. This grommet insures that water and dust does not enter the luminaire through the knockout hole in the back of the luminaire. Consult factory for mixing reflector and lamp options.




Product Family








UTA-30723-W




Tango 11 square wall up-down light

Model No.	Lamp	Holder	Beam	Lumen	Weight	(H) Height
UTA-30721	CFQ 2X18w.	G24q-2	88°	2X1075	13.4 lb.	16.22"
UTA-30722	T6 CMH 39w.	G12	54°	2720	10.5 lb.	7.8"
UTA-30723-VN	T6 CMH 2X39w.	G12	6°	2X2720	17.8 lb.	18.98"
UTA-30723-N	T6 CMH 2X39w.	G12	12°	2X2720	17.8 lb.	18.98"
UTA-30723-M	T6 CMH 2X39w.	G12	26°	2X2720	17.8 lb.	18.98"
UTA-30723-W	T6 CMH 2X39w.	G12	35°	2X2720	17.8 lb.	18.98"
UTA-30723-VW	T6 CMH 2X39w.	G12	60°	2X2720	17.8 lb.	18.98"






UTA-30737-W







Tango 12 square wall up-down light

Model No.	Lamp	Holder	Beam	Lumen	Weight	(H) Height
UTA-30731	CFQ 2X26w./CFTR 2X32/42w.	Gx24q-3/4	79°/74°/79°	2X1550/2X2040/2x2720	17.2 lb.	18.74"
UTA-30732	PMH-ED17 2X70w.	MED	67°	2X4000	26.6 lb.	22.32"
UTA-30733	HPS-ED17 2X70w.	MED	79°	2X5450	26.6 lb.	22.32"
UTA-30734-N	T6 CMH 70w.	G12	18°	5600	15.6 lb.	10.31"
UTA-30734-W	T6 CMH 70w.	G12	59°	5600	15.6 lb.	10.31"
UTA-30735-VN	T6 CMH 2X70w.	G12	6°	2X5600	25.5 lb.	25.5"
UTA-30735-N	T6 CMH 2X70w.	G12	12°	2X5600	25.5 lb.	25.5"
UTA-30735-M	T6 CMH 2X70w.	G12	26°	2X5600	25.5 lb.	25.5"
UTA-30735-W	T6 CMH 2X70w.	G12	35°	2X5600	25.5 lb.	25.5"
UTA-30735-VW	T6 CMH 2X70w.	G12	60°	2X5600	25.5 lb.	25.5"
UTA-30736-N	T6 CMH 100w.	G12	18°	7600	15.6 lb.	10.31"
UTA-30736-W	T6 CMH 100w.	G12	59°	7600	15.6 lb.	10.31"
UTA-30737-N	T6 CMH 150w.	G12	18°	11500	15.6 lb.	10.31"
UTA-30737-W	T6 CMH 150w.	G12	59°	11500	15.6 lb.	10.31"



Tango 9, 10 square wall up-down light


IP65   /EN 60598/CLASS I  //IK10





Suitable for wet locations

Wall luminaires with upward and downward light distributions. The upward light illuminate very sharp light distribution by a glass lens. Ideal is designed to illuminate the wall and surface in front of wall and for light accents on vertical surfaces.

Die-cast aluminium housing with high corrosion resistance. Aluminium bottom frame with integral anti-glare baffle. Stainless steel screws. Durable silicone rubber gasket and clear toughened glass. Single cable entry with electrical wiring fast connectors. Powder paint with high corrosion resistance with chemical chromatised protection. Integral control gear. Anodized high purity aluminium reflector design for two directionals up and down light distribution use one lamp. To maintain the integrity of the IP rating of this luminaire it is supplied with a specially designed SHG self sealing wiring grommet that is used when connecting to the power supply. This grommet insures that water and dust does not enter the luminaire through the knockout hole in the back of the luminaire.




Product Family








UTA-30861-W





Tango 9 square wall up-down light


Model No.	Lamp	Holder	Beam	Lumen	Weight
UTA-30861-R	T6 CMH 39w.	G12	3.5°/32°	2720	11.9 lb.
UTA-30861-B	T6 CMH 39w.	G12	3.5°/32°	2720	11.9 lb.
UTA-30861-Y	T6 CMH 39w.	G12	3.5°/32°	2720	11.9 lb.
UTA-30861-G	T6 CMH 39w.	G12	3.5°/32°	2720	11.9 lb.
UTA-30861-W	T6 CMH 39w.	G12	3.5°/32°	2720	11.9 lb.



Top view




Mounting detail



Bottom view






UTA-30871-W




Tango 10 square wall up-down light


Model No.	Lamp	Holder	Beam	Lumen	Weight
UTA-30871-R	T6 CMH 70w.	G12	3.5°/34°	5600	16.3 lb.
UTA-30871-B	T6 CMH 70w.	G12	3.5°/34°	5600	16.3 lb.
UTA-30871-Y	T6 CMH 70w.	G12	3.5°/34°	5600	16.3 lb.
UTA-30871-G	T6 CMH 70w.	G12	3.5°/34°	5600	16.3 lb.
UTA-30871-W	T6 CMH 70w.	G12	3.5°/34°	5600	16.3 lb.
UTA-30872-R	T6 CMH 100w.	G12	4°/36°	7600	17.6 lb.
UTA-30872-B	T6 CMH 100w.	G12	4°/36°	7600	17.6 lb.
UTA-30872-Y	T6 CMH 100w.	G12	4°/36°	7600	17.6 lb.
UTA-30872-G	T6 CMH 100w.	G12	4°/36°	7600	17.6 lb.
UTA-30872-W	T6 CMH 100w.	G12	4°/36°	7600	17.6 lb.
UTA-30873-R	T6 CMH 150w.	G12	4°/36°	11500	17.6 lb.
UTA-30873-B	T6 CMH 150w.	G12	4°/36°	11500	17.6 lb.
UTA-30873-Y	T6 CMH 150w.	G12	4°/36°	11500	17.6 lb.
UTA-30873-G	T6 CMH 150w.	G12	4°/36°	11500	17.6 lb.
UTA-30873-W	T6 CMH 150w.	G12	4°/36°	11500	17.6 lb.



Top view



Mounting detail



Bottom view

Tango 3, 4 cylindrical wall down light


IP65 ⚡⚡/EN 60598/CLASS I ⚡/V/CE/IK10




Suitable for wet locations

Wall luminaires with options of reflector and beam distribution downward light distributions. Ideal is designed to illuminate the wall and surface in front of wall and for light accents on vertical surfaces.

Die-cast aluminium housing with high corrosion resistance. Aluminium bottom frame with integral anti-glare baffles. Stainless steel screws. Durable silicone rubber gasket and clear toughened glass. Single cable entry with electrical wiring fast connectors. Powder paint with high corrosion resistance with chemical chromatised protection. Integral control gear. Anodized high purity aluminium reflector. To maintain the integrity of the IP rating of this luminaire it is supplied with a specially designed SHG self sealing wiring grommet that is used when connecting to the power supply. This grommet insures that water and dust does not enter the luminaire through the knockout hole in the back of the luminaire.




Product Family








UTA-30412-W



Tango 3 cylindrical wall down light





Model No.	Lamp	Holder	Beam	Lumen	Weight
UTA-30411	CFQ 18w.	G24q-2	88°	1075	7.0 lb.
UTA-30412-VN	T6 CMH 39w.	G12	6°	2720	8.6 lb.
UTA-30412-N	T6 CMH 39w.	G12	12°	2720	8.6 lb.
UTA-30412-M	T6 CMH 39w.	G12	26°	2720	8.6 lb.
UTA-30412-W	T6 CMH 39w.	G12	35°	2720	8.6 lb.
UTA-30412-VW	T6 CMH 39w.	G12	60°	2720	8.6 lb.



UTA-30391

Tango 4 cylindrical wall down light

Model No.	Lamp	Holder	Beam	Lumen	Weight
UTA-30391	CFQ 26w./CFTR 32/42w.	Gx24q-3/4	79°/74°/79°	1550/2040/2720	8.8 lb.
UTA-30392-70	PMH-ED17 70w.	MED	67°	4000	12.5 lb.
UTA-30392-100	PMH-ED17 100w.	MED	67°	6500	12.7 lb.
UTA-30393-70	HPS-ED17 70w.	MED	79°	5450	12.5 lb.
UTA-30393-100	HPS-ED17 100w.	MED	67°	8550	13.0 lb.
UTA-30394-VN	T6 CMH 70w.	G12	6°	5600	12.7 lb.
UTA-30394-N	T6 CMH 70w.	G12	12°	5600	12.7 lb.
UTA-30394-M	T6 CMH 70w.	G12	26°	5600	12.7 lb.
UTA-30394-W	T6 CMH 70w.	G12	35°	5600	12.7 lb.
UTA-30394-VW	T6 CMH 70w.	G12	60°	5600	12.7 lb.
UTA-30395-VN	T6 CMH 100w.	G12	10°	7600	13.8 lb.
UTA-30395-N	T6 CMH 100w.	G12	12°	7600	13.8 lb.
UTA-30395-M	T6 CMH 100w.	G12	30°	7600	13.8 lb.
UTA-30395-W	T6 CMH 100w.	G12	40°	7600	13.8 lb.
UTA-30395-VW	T6 CMH 100w.	G12	64°	7600	13.8 lb.
UTA-30396-VN	T6 CMH 150w.	G12	10°	11500	13.8 lb.
UTA-30396-N	T6 CMH 150w.	G12	12°	11500	13.8 lb.
UTA-30396-M	T6 CMH 150w.	G12	30°	11500	13.8 lb.
UTA-30396-W	T6 CMH 150w.	G12	40°	11500	13.8 lb.
UTA-30396-VW	T6 CMH 150w.	G12	64°	11500	13.8 lb.



(VN) Very Narrow beam (N) Narrow beam (M) Medium beam (W) Wide beam (VW) Very Wide beam


Tango 13, 14 square wall down light

IP65 ◆ ▲ ▲ /EN 60598/CLASS I ⚡ /▽/CE/IK10





Suitable for wet locations

Wall luminaires with a selection of lamps and reflectors offering different beam distributions for various downward lighting requirements. Designed to illuminate the wall surface and for light accents on vertical surfaces. Low copper content die-cast aluminum housing and aluminum frame with integral anti-glare baffles. Stainless steel screws. Durable silicone rubber gasket and clear toughened glass. Single cable entry. Housing is treated with a chemical chromated protection before powder coating, ensuring high corrosion resistance. Integral control gear. Anodized high purity aluminum reflector. To maintain the integrity of the IP rating of this luminaire it is supplied with a specially designed SHG self sealing wiring grommet that is used when connecting to the power supply. This grommet insures that water and dust does not enter the luminaire through the knockout hole in the back of the luminaire.




Product Family








UTA-30741



Tango 13 square wall down light




Model No.	Lamp	Holder	Beam	Lumen	Weight
UTA-30741	CFQ 18w.	G24q-2	88°	1075	8.3 lb.
UTA-30742-VN	T6 CMH 39w.	G12	6°	2720	9.9 lb.
UTA-30742-N	T6 CMH 39w.	G12	12°	2720	9.9 lb.
UTA-30742-M	T6 CMH 39w.	G12	26°	2720	9.9 lb.
UTA-30742-W	T6 CMH 39w.	G12	35°	2720	9.9 lb.
UTA-30742-VW	T6 CMH 39w.	G12	60°	2720	9.9 lb.




UTA-30754

Tango 14 square wall down light

Model No.	Lamp	Holder	Beam	Lumen	Weight
UTA-30751	CFQ 26w./CFTR 32/42w.	Gx24q-3/4	79°/74°/79°	1550/2040/2720	11.0 lb.
UTA-30752-70	PMH-ED17 70w.	MED	67°	4000	14.7 lb.
UTA-30752-100	PMH-ED17 100w.	MED	67°	6500	14.9 lb.
UTA-30753-70	HPS-ED17 70w.	MED	79°	5450	14.7 lb.
UTA-30753-100	HPS-ED17 100w.	MED	67°	8550	15.2 lb.
UTA-30754-VN	T6 CMH 70w.	G12	6°	5600	14.9 lb.
UTA-30754-N	T6 CMH 70w.	G12	12°	5600	14.9 lb.
UTA-30754-M	T6 CMH 70w.	G12	26°	5600	14.9 lb.
UTA-30754-W	T6 CMH 70w.	G12	35°	5600	14.9 lb.
UTA-30754-VW	T6 CMH 70w.	G12	60°	5600	14.9 lb.
UTA-30755-VN	T6 CMH 100w.	G12	10°	7600	16.0 lb.
UTA-30755-N	T6 CMH 100w.	G12	12°	7600	16.0 lb.
UTA-30755-M	T6 CMH 100w.	G12	30°	7600	16.0 lb.
UTA-30755-W	T6 CMH 100w.	G12	40°	7600	16.0 lb.
UTA-30755-VW	T6 CMH 100w.	G12	64°	7600	16.0 lb.
UTA-30756-VN	T6 CMH 150w.	G12	10°	11500	16.0 lb.
UTA-30756-N	T6 CMH 150w.	G12	12°	11500	16.0 lb.
UTA-30756-M	T6 CMH 150w.	G12	30°	11500	16.0 lb.
UTA-30756-W	T6 CMH 150w.	G12	40°	11500	16.0 lb.
UTA-30756-VW	T6 CMH 150w.	G12	64°	11500	16.0 lb.



(VN) Very Narrow beam (N) Narrow beam (M) Medium beam (W) Wide beam (VW) Very Wide beam



Product Family



Tango cylindrical and square wall down light HP LED

IP65 /EN 60598/CLASS I //CE /IK10



Suitable for wet locations


Wall luminaires with a selection of beam distributions for various downward lighting requirements. Designed to illuminate the wall surface and for light accents on vertical surfaces. They are suitable for many applications such as residential and pedestrian areas, shopping malls, parks and gardens, as well as commercial, historic or modern architectural interiors and exteriors. The luminaires have features such as long life, limited maintenance and constant lifetime performance. The cool lens is perfect for public and pedestrian areas. The luminaires use a high quality LED source with low energy consumption.

The Luminaire is rated as class I with the LED integral driver. Low copper content die-cast aluminum housing and frame. Stainless steel screws. Durable silicone rubber gasket and clear toughened glass. Single cable entry. Housing is treated with a chemical chromated protection before powder coating, ensuring high corrosion resistance. To maintain the integrity of the IP rating of this luminaire it is supplied with a specially designed SHG self sealing wiring grommet that is used when connecting to the power supply. This grommet insures that water and dust does not enter the luminaire through the knockout hole in the back of the luminaire.





UTA-31781-N-W27




Tango Cylindrical wall down light dia 6.3" HP LED

Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UTA-31781-N-W27	18 LED	1826 lm	2700K	30	14°	7.5 lb.	•
UTA-31781-N-W30	18 LED	1917 lm	3000K	30	14°	7.5 lb.	•
UTA-31781-N-W40	18 LED	1943 lm	4000K	30	14°	7.5 lb.	•
UTA-31781-M-W27	18 LED	1781 lm	2700K	30	24°	7.5 lb.	•
UTA-31781-M-W30	18 LED	1895 lm	3000K	30	24°	7.5 lb.	•
UTA-31781-M-W40	18 LED	2072 lm	4000K	30	24°	7.5 lb.	•
UTA-31781-W-W27	18 LED	1712 lm	2700K	30	40°	7.5 lb.	•
UTA-31781-W-W30	18 LED	1822 lm	3000K	30	40°	7.5 lb.	•
UTA-31781-W-W40	18 LED	1933 lm	4000K	30	40°	7.5 lb.	•









UTA-31801-M-W30




Tango Square wall down light 6.3" HP LED


Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UTA-31801-N-W27	18 LED	1826 lm	2700K	30	14°	8.82 lb.	•
UTA-31801-N-W30	18 LED	1917 lm	3000K	30	14°	8.82 lb.	•
UTA-31801-N-W40	18 LED	1943 lm	4000K	30	14°	8.82 lb.	•
UTA-31801-M-W27	18 LED	1781 lm	2700K	30	24°	8.82 lb.	•
UTA-31801-M-W30	18 LED	1895 lm	3000K	30	24°	8.82 lb.	•
UTA-31801-M-W40	18 LED	2072 lm	4000K	30	24°	8.82 lb.	•
UTA-31801-W-W27	18 LED	1712 lm	2700K	30	40°	8.82 lb.	•
UTA-31801-W-W30	18 LED	1822 lm	3000K	30	40°	8.82 lb.	•
UTA-31801-W-W40	18 LED	1933 lm	4000K	30	40°	8.82 lb.	•



(N), (M), (W) beam in 3000K



(N), (M), (W) beam in 4000K



Lighting Simulation


Tango Wall Light LED



Lighting Simulation : Architectural Building


Luminaire : Tango Wall Down LED 3000K

- UTA-31801-N 18 LED (Narrow beam)
- UTA-31801-M 18 LED (Medium beam)
- UTA-31801-W 18 LED (Wide beam)




False color analysis in lux

LUMINAIRE



Luminaire : Tango Wall Down LED 3000K

- UTA-31801-N 18 LED (Narrow beam)
- UTA-31801-M 18 LED (Medium beam)
- UTA-31801-W 18 LED (Wide beam)



*Ambient light setting set to sunset time.

*The colors and brightness generated by simulation software are for explanatory purpose only and may differ from actual product specification.

Lighting Simulation


Tango Wall Light LED



Lighting Simulation : Architectural Building

Luminaire : Tango Wall Up-Down LED 3000K

- UTA-31851-N 24 LED (Narrow beam)



False color analysis in lux

LUMINAIRE



Luminaire : Tango Wall Up-Down LED 3000K

- UTA-31851-N 24 LED (Narrow beam)




*Ambient light setting set to sunset time.

*The colors and brightness generated by simulation software are for explanatory purpose only and may differ from actual product specification.



UTA-31821-M-W30




Tango Cylindrical wall down light dia 7.32" HP LED

Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UTA-31821-N-W27	24 LED	2392 lm	2700K	40	14°	9.7 lb.	•
UTA-31821-N-W30	24 LED	2545 lm	3000K	40	14°	9.7 lb.	•
UTA-31821-N-W40	24 LED	2750 lm	4000K	40	14°	9.7 lb.	•
UTA-31821-M-W27	24 LED	2568 lm	2700K	40	25°	9.7 lb.	•
UTA-31821-M-W30	24 LED	2570 lm	3000K	40	25°	9.7 lb.	•
UTA-31821-M-W40	24 LED	2585 lm	4000K	40	25°	9.7 lb.	•
UTA-31821-W-W27	24 LED	2295 lm	2700K	40	40°	9.7 lb.	•
UTA-31821-W-W30	24 LED	2442 lm	3000K	40	40°	9.7 lb.	•
UTA-31821-W-W40	24 LED	2488 lm	4000K	40	40°	9.7 lb.	•





UTA-31841-W-W30




Tango Square wall down light 7.32" HP LED


Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UTA-31841-N-W27	24 LED	2392 lm	2700K	40	14°	14.3 lb.	•
UTA-31841-N-W30	24 LED	2545 lm	3000K	40	14°	14.3 lb.	•
UTA-31841-N-W40	24 LED	2750 lm	4000K	40	14°	14.3 lb.	•
UTA-31841-M-W27	24 LED	2568 lm	2700K	40	25°	14.3 lb.	•
UTA-31841-M-W30	24 LED	2570 lm	3000K	40	25°	14.3 lb.	•
UTA-31841-M-W40	24 LED	2585 lm	4000K	40	25°	14.3 lb.	•
UTA-31841-W-W27	24 LED	2295 lm	2700K	40	40°	14.3 lb.	•
UTA-31841-W-W30	24 LED	2442 lm	3000K	40	40°	14.3 lb.	•
UTA-31841-W-W40	24 LED	2488 lm	4000K	40	40°	14.3 lb.	•





(N) Narrow beam




(M) Medium beam




(W) Wide beam




(N), (M), (W) beam in 3000K




(N), (M), (W) beam in 4000K







UTA-31285-N



Tango cylindrical wall down light dia 6.3" HP LED




Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UTA-31285-VN-W27	9 LED	817 lm	2700K	17	9°	7.5 lb.	•
UTA-31285-VN-W30	9 LED	821 lm	3000K	17	9°	7.5 lb.	•
UTA-31285-VN-W40	9 LED	939 lm	4000K	17	9°	7.5 lb.	•
UTA-31285-N-W27	9 LED	716 lm	2700K	17	13°	7.5 lb.	•
UTA-31285-N-W30	9 LED	720 lm	3000K	17	13°	7.5 lb.	•
UTA-31285-N-W40	9 LED	823 lm	4000K	17	13°	7.5 lb.	•
UTA-31285-M-W27	9 LED	751 lm	2700K	17	23°	7.5 lb.	•
UTA-31285-M-W30	9 LED	755 lm	3000K	17	23°	7.5 lb.	•
UTA-31285-M-W40	9 LED	863 lm	4000K	17	23°	7.5 lb.	•
UTA-31285-W-W27	9 LED	776 lm	2700K	17	32°	7.5 lb.	•
UTA-31285-W-W30	9 LED	780 lm	3000K	17	32°	7.5 lb.	•
UTA-31285-W-W40	9 LED	892 lm	4000K	17	32°	7.5 lb.	•



UTA-31295-W

Tango Square wall down light 6.3" HP LED

Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UTA-31295-VN-W27	9 LED	817 lm	2700K	17	9°	8.8 lb.	•
UTA-31295-VN-W30	9 LED	821 lm	3000K	17	9°	8.8 lb.	•
UTA-31295-VN-W40	9 LED	939 lm	4000K	17	9°	8.8 lb.	•
UTA-31295-N-W27	9 LED	716 lm	2700K	17	13°	8.8 lb.	•
UTA-31295-N-W30	9 LED	720 lm	3000K	17	13°	8.8 lb.	•
UTA-31295-N-W40	9 LED	823 lm	4000K	17	13°	8.8 lb.	•
UTA-31295-M-W27	9 LED	751 lm	2700K	17	23°	8.8 lb.	•
UTA-31295-M-W30	9 LED	755 lm	3000K	17	23°	8.8 lb.	•
UTA-31295-M-W40	9 LED	863 lm	4000K	17	23°	8.8 lb.	•
UTA-31295-W-W27	9 LED	776 lm	2700K	17	32°	8.8 lb.	•
UTA-31295-W-W30	9 LED	780 lm	3000K	17	32°	8.8 lb.	•
UTA-31295-W-W40	9 LED	892 lm	4000K	17	32°	8.8 lb.	•



(VN) Very narrow beam 9°

(N) Narrow beam 13°

(M) Medium beam 23°

(W) Wide beam 32°



Tango cylindrical and square wall up-down light HP LED


IP65 ◆ ▲ ▲ /EN 60598/CLASS I Ⓢ / ▽ / CE / IK10




Suitable for wet locations

Wall luminaires with a selection of beam distributions for various up and downward lighting requirements. Designed to illuminate the wall surface and for light accents on vertical surfaces. They are suitable for many applications like, residential and pedestrian areas , shopping malls, parks and gardens as well as commercial, historic or modern architectural interiors and exteriors. The luminaires have features such as long life, limited maintenance and constant lifetime performance. The cool lens is perfect for public and pedestrian areas. The luminaires use a high quality LED source with low energy consumption.

The Luminaire is rated as class I with the LED integral driver. Low copper content die-cast aluminum housing and aluminum bottom frame with integral anti-glare baffles. Stainless steel screws. Durable silicone rubber gasket and clear toughened glass. Single cable entry. Housing is treated with a chemical chromated protection before powder coating, ensuring high corrosion resistance. To maintain the integrity of the IP rating of this luminaire it is supplied with a specially designed SHG self sealing wiring grommet that is used when connecting to the power supply. This grommet insures that water and dust does not enter the luminaire through the knockout hole in the back of the luminaire.




Product Family





UTA-31791-M-W27




Tango Cylindrical wall up-down light dia 6.3" HP LED

Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UTA-31791-N-W27	2x18 LED	2x1826 lm	2700K	2x30	14°	11.4 lb.	•
UTA-31791-N-W30	2x18 LED	2x1917 lm	3000K	2x30	14°	11.4 lb.	•
UTA-31791-N-W40	2x18 LED	2x1943 lm	4000K	2x30	14°	11.4 lb.	•
UTA-31791-M-W27	2x18 LED	2x1781 lm	2700K	2x30	24°	11.4 lb.	•
UTA-31791-M-W30	2x18 LED	2x1895 lm	3000K	2x30	24°	11.4 lb.	•
UTA-31791-M-W40	2x18 LED	2x2072 lm	4000K	2x30	24°	11.4 lb.	•
UTA-31791-W-W27	2x18 LED	2x1712 lm	2700K	2x30	40°	11.4 lb.	•
UTA-31791-W-W30	2x18 LED	2x1822 lm	3000K	2x30	40°	11.4 lb.	•
UTA-31791-W-W40	2x18 LED	2x1933 lm	4000K	2x30	40°	11.4 lb.	•





UTA-31811-N-W27




Tango Square wall up-down light 6.3" HP LED


Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UTA-31811-N-W27	2x18 LED	2x1826 lm	2700K	2x30	14°	14.7 lb.	•
UTA-31811-N-W30	2x18 LED	2x1917 lm	3000K	2x30	14°	14.7 lb.	•
UTA-31811-N-W40	2x18 LED	2x1943 lm	4000K	2x30	14°	14.7 lb.	•
UTA-31811-M-W27	2x18 LED	2x1781 lm	2700K	2x30	24°	14.7 lb.	•
UTA-31811-M-W30	2x18 LED	2x1895 lm	3000K	2x30	24°	14.7 lb.	•
UTA-31811-M-W40	2x18 LED	2x2072 lm	4000K	2x30	24°	14.7 lb.	•
UTA-31811-W-W27	2x18 LED	2x1712 lm	2700K	2x30	40°	14.7 lb.	•
UTA-31811-W-W30	2x18 LED	2x1822 lm	3000K	2x30	40°	14.7 lb.	•
UTA-31811-W-W40	2x18 LED	2x1933 lm	4000K	2x30	40°	14.7 lb.	•





(N) Narrow beam




(M) Medium beam




(W) Wide beam



(N), (M), (W) beam in 3000K




(N), (M), (W) beam in 4000K





UTA-31831-N-W27




Tango Cylindrical wall up-down light dia 7.32" HP LED

Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UTA-31831-N-W27	2x24 LED	2x2392 lm	2700K	2x40	14°	14.1 lb.	•
UTA-31831-N-W30	2x24 LED	2x2545 lm	3000K	2x40	14°	14.1 lb.	•
UTA-31831-N-W40	2x24 LED	2x2750 lm	4000K	2x40	14°	14.1 lb.	•
UTA-31831-M-W27	2x24 LED	2x2568 lm	2700K	2x40	25°	14.1 lb.	•
UTA-31831-M-W30	2x24 LED	2x2570 lm	3000K	2x40	25°	14.1 lb.	•
UTA-31831-M-W40	2x24 LED	2x2585 lm	4000K	2x40	25°	14.1 lb.	•
UTA-31831-W-W27	2x24 LED	2x2295 lm	2700K	2x40	40°	14.1 lb.	•
UTA-31831-W-W30	2x24 LED	2x2442 lm	3000K	2x40	40°	14.1 lb.	•
UTA-31831-W-W40	2x24 LED	2x2488 lm	4000K	2x40	40°	14.1 lb.	•






UTA-31851-W-W27




Tango Square wall up-down light 7.32" HP LED


Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UTA-31851-N-W27	2x24 LED	2x2392 lm	2700K	2x40	14°	18.5 lb.	•
UTA-31851-N-W30	2x24 LED	2x2545 lm	3000K	2x40	14°	18.5 lb.	•
UTA-31851-N-W40	2x24 LED	2x2750 lm	4000K	2x40	14°	18.5 lb.	•
UTA-31851-M-W27	2x24 LED	2x2568 lm	2700K	2x40	25°	18.5 lb.	•
UTA-31851-M-W30	2x24 LED	2x2570 lm	3000K	2x40	25°	18.5 lb.	•
UTA-31851-M-W40	2x24 LED	2x2585 lm	4000K	2x40	25°	18.5 lb.	•
UTA-31851-W-W27	2x24 LED	2x2295 lm	2700K	2x40	40°	18.5 lb.	•
UTA-31851-W-W30	2x24 LED	2x2442 lm	3000K	2x40	40°	18.5 lb.	•
UTA-31851-W-W40	2x24 LED	2x2488 lm	4000K	2x40	40°	18.5 lb.	•





(N) Narrow beam




(M) Medium beam




(W) Wide beam




(N), (M), (W) beam in 3000K




(N), (M), (W) beam in 4000K



Mounting detail






UTA-31305-W-W30




Tango cylindrical wall up-down light dia 6.3" HP LED



Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UTA-31305-VN-W27	2x9 LED	2x817 lm	2700K	2x17	9°	8.16 lb.	•
UTA-31305-VN-W30	2x9 LED	2x821 lm	3000K	2x17	9°	8.16 lb.	•
UTA-31305-VN-W40	2x9 LED	2x939 lm	4000K	2x17	9°	8.16 lb.	•
UTA-31305-N-W27	2x9 LED	2x716 lm	2700K	2x17	13°	8.16 lb.	•
UTA-31305-N-W30	2x9 LED	2x720 lm	3000K	2x17	13°	8.16 lb.	•
UTA-31305-N-W40	2x9 LED	2x823 lm	4000K	2x17	13°	8.16 lb.	•
UTA-31305-M-W27	2x9 LED	2x751 lm	2700K	2x17	23°	8.16 lb.	•
UTA-31305-M-W30	2x9 LED	2x755 lm	3000K	2x17	23°	8.16 lb.	•
UTA-31305-M-W40	2x9 LED	2x863 lm	4000K	2x17	23°	8.16 lb.	•
UTA-31305-W-W27	2x9 LED	2x776 lm	2700K	2x17	32°	8.16 lb.	•
UTA-31305-W-W30	2x9 LED	2x780 lm	3000K	2x17	32°	8.16 lb.	•
UTA-31305-W-W40	2x9 LED	2x892 lm	4000K	2x17	32°	8.16 lb.	•




Top view



Bottom view




UTA-31315-W-W30




Tango square wall up-down light 6.3" HP LED


Model No.	Lamp	Light output	LED colour	Power W	Beam	Weight	Dimmable 1-10V
UTA-31315-VN-W27	2x9 LED	2x817 lm	2700K	2x17	9°	11.0 lb.	•
UTA-31315-VN-W30	2x9 LED	2x821 lm	3000K	2x17	9°	11.0 lb.	•
UTA-31315-VN-W40	2x9 LED	2x939 lm	4000K	2x17	9°	11.0 lb.	•
UTA-31315-N-W27	2x9 LED	2x716 lm	2700K	2x17	13°	11.0 lb.	•
UTA-31315-N-W30	2x9 LED	2x720 lm	3000K	2x17	13°	11.0 lb.	•
UTA-31315-N-W40	2x9 LED	2x823 lm	4000K	2x17	13°	11.0 lb.	•
UTA-31315-M-W27	2x9 LED	2x751 lm	2700K	2x17	23°	11.0 lb.	•
UTA-31315-M-W30	2x9 LED	2x755 lm	3000K	2x17	23°	11.0 lb.	•
UTA-31315-M-W40	2x9 LED	2x863 lm	4000K	2x17	23°	11.0 lb.	•
UTA-31315-W-W27	2x9 LED	2x776 lm	2700K	2x17	32°	11.0 lb.	•
UTA-31315-W-W30	2x9 LED	2x780 lm	3000K	2x17	32°	11.0 lb.	•
UTA-31315-W-W40	2x9 LED	2x892 lm	4000K	2x17	32°	11.0 lb.	•



Top view



Bottom view



Mounting detail