# LUMINAIRE SPECIFICATION

Head Office:
7144 NW Progress Ct
Hillsboro, Oregon 97124
Tel: 503-645-0500
Fax: 503-645-8100
www.ligmanlightingusa.com

IP55 : Suitable for Wet Locations
IK07 : Impact Resistant (Vandal Resistant)



# UDU-20021

## Duomo double small shade post top

A post top luminaire with a small and medium size shade decorative lantern and symmetrical light distribution. It uses energy saving LED, compact fluorescent lamps as well as metal halide and high pressure sodium lamps. Developed to compliment the Duomo wall light, Duomo bollard and Duomo pillar light. Designed for lighting car parks, footpaths, pedestrian areas, precincts, parks, gardens and building perimeters. Low copper content die cast housing with high corrosion resistance. Stainless steel screws. Durable silicone rubber gasket and opal glass diffuser. Housing is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral electronic control gear.

### Physical Data

Length: 35.3″
Height: 13.3″
Weight: 55.3 lbs

### Lamp

☐ CFQ 2x13w

(For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)


### Voltage (Please Specify)

☐ 120V
☐ 277V
☐ Other _____

### Options (Please Specify)

Color (Please Specify)

☐ 01-Black - RAL 9011
☐ 02- Dark Grey - RAL 7043
☐ 03-White - RAL 9003
☐ 04 - Metallic Silver - RAL 9006
☐ 05-Matt Silver - RAL 9006
☐ 07- Custom - RAL _____
☐ 06-Bronze - RAL 6014




Shade Style



☐ (1) Swept Shade



☐ (2) Straight Shade



☐ DS- Dark Sky Compliant


☐ HGT - Specify Pole Height _____ ft




☐ Single Banner Arm



☐ Double Banner Arm













*Ordering Example : UDU - 20021 - CFQ - 2x13w - 120v - Options*

PROJECT: _____ DATE: _____

TYPE: _____ QUANTITY: _____ NOTE: _____

Ligman Lighting USA reserves the right to change specifications without prior notice, please contact factory for latest information.
Due to the continual improvements in LED technology data and components may change without notice.