



INSTALLATION AND SERVICE MANUAL

For installation of Large Atlantic dia 27.56" sheppards crook wall streetlighting LED.
Model. UAA-30640.


Product drawing (dimensions)




SUITABLE FOR WET LOCATIONS



NOTE
Mounts over
a 3" Octagonal
Junction box.




②




Install Gasket between wall
and Back Plate.

③



Position the Back Plate
over the J Box and Secure
the back plate to the wall

④



Notice to installer :

- 1. WIRING INSTRUCTIONS** Warning : RISK OF FIRE AND ELECTRICAL SHOCK. : FIXTURE MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN ONLY>FIXTURE IS INTENDED FOR INSTALLATION IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, LOCAL AND FEDERAL CODE SPECIFICATIONS. DISCONNECT POWER BEFORE SERVICING.
- 2. This fixture has a VOLTAGE SPECIFIC BALLAST, Check that the supply voltage is the same as the installed ballast voltage.**

Ligman Lighting USA

7144 NW Progress Court, Hillsboro
Oregon, 97124, USA
Tel : 503 645 0500 | Fax : 503 645 8100

www.ligmanlightingusa.com

UAA-30640 15/09/17/REV.0 1/2 PIM

ISO 9001
ISO 14001
BUREAU VERITAS
Certification



FM-TS-13/25-05-2007-REV.2

